mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



muRata Capacitor Data Sheet RPER71H222K2P1A03B "#" indicates a package specification code.					
Discontinued General AEC- Q200 125 Anti- crack	Soldering Crack Flow OK Welding R	OHS REACH			
< List of part numbers with package codes > RPER71H222K2P1A03B					
Shape		Notes			
		In case of automotive use, alternative part is RCE series.			
	<u>a</u>	References			
		Packaging	Specifications	Minimum quantity	
		В	Packing in bulk	500	
Coating extension does not exceed the end of the lead bend. Lead Wire : Solder Coated Copper Wire or Solder Coated CP Wire (in mm)					
L size or outer diameter D (mm)	5.0 mm max.				
W size	3.5 mm max.				
T size	2.5 mm max.				
Lead spacing F	2.5 ±0.8mm				
Lead diameter d	0.5 ±0.05mm				

Specifications

W1 size (max.)

Capacitance	2200pF±10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

5.0mm

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.