



Wire ————— Cu tinned
 Gauge ————— AWG 28/7
 Voltage rating ————— 300 Vr.m.s
 Current (Max) ————— 2,1A
 Conductor resistance ————— 221 mΩ/m
 Capacity unbalanced ————— 42,7 pF/m
 Impedance unbalanced ————— 105 Ω
 Inductance unbalanced ————— 0,68 μH/m
 Signal delay ————— 4,9 ns/m
 Insulation material ————— PVC
 Temperature rating ————— | -20°C (operating) to 105°C
 | -30°C (static)
 Flammability rating ————— UL: VW1
 Insulation resistance ————— 100 MΩ/km
 Approval ————— UL AWM style 2651

Colour code sequence (in 10 steps):

- brown
- red
- orange
- yellow
- green
- blue
- violet
- grey
- white
- black

				Dot.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 Flat cable	Maßstab/ Scale	
			Detail.	20/10/05	JMDR		14 poles, length per reel: 30,48 m colour coded, UL 20130, IEC 918	10:1	
			Insp.						
EC01446	22/02/10	SC	Stand.						
							TB 09 18 014 7005	Blatt/ Page	
								HARTING EURL F-95972 Paris	1 / 1