



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





TEL: 973-328-3200 FAX: 973-328-31

DAFLEX Braided Fiberglass Sleeving UL VW-1

For High Temperature Applications to 1200°F

Description: Daflex D1200 sleeving is an extremely flexible, tightly braided class C fiberglass sleeving. It is non-flammable and treated for removal of all organic matter. The glass braid is fray resistant and non-corroding. It will provide maximum mechanical strength.

Dielectric strength determined by space factor.

It will not support combustion or fungus growth.

This series is RoHS compliant.

DAFLEX Catalog No.	Size	Nom. I.D.		Std. Spool or Coil
		IN.	MM.	
D1200-24	24	0.022	0.56	100', 1000'*
D1200-22	22	0.027	0.69	100', 1000'*
D1200-20	20	0.034	0.86	100', 1000'*
D1200-18	18	0.042	1.07	100', 1000'*
D1200-17	17	0.047	1.19	100', 1000'*
D1200-16	16	0.053	1.35	100', 1000'*
D1200-15	15	0.059	1.50	100', 1000'*
D1200-14	14	0.066	1.68	100', 1000'*
D1200-13	13	0.076	1.93	100', 1000'*
D1200-12	12	0.085	2.16	100', 500'*
D1200-11	11	0.095	2.41	100'*
D1200-10	10	0.106	2.69	100', 500'*
D1200-9	9	0.118	3.00	100'*
D1200-8	8	0.133	3.38	100', 500'*
D1200-7	7	0.148	3.76	100'*
D1200-6	6	0.166	4.22	100', 500'*
D1200-5	5	0.186	4.72	100'*
D1200-4	4	0.208	5.28	100', 500'*
D1200-3	3	0.234	5.94	100'*
D1200-2	2	0.263	6.68	100', 500'*
D1200-1	1	0.294	7.47	100'
D1200-0	0	0.330	8.38	100'
D1200-3/8	3/8"	0.387	9.83	100'
D1200-7/16	7/16"	0.450	11.43	100'
D1200-1/2	1/2"	0.512	13.00	100'
D1200-5/8	5/8"	0.640	16.26	100'
D1200-3/4	3/4"	0.768	19.51	100'
D1200-7/8	7/8"	0.893	22.68	100'
D1200-1"	1"	1.018	25.86	100'

* Preferred Put Up

Standard Color: Natural.

Applicable Specs:NEMA VS-1 1962. Class C, UL STD 1441.