## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# **3**M



# Automotive Acrylic *Plus* Attachment Tape

Part Numbers 06382, 06383, 06384 and 06386 (Black)

Technical Data Sheet	July 2002				
General Description	3M <sup>™</sup> Automotive Acrylic <i>Plus</i> Attachment Tape Part Numbers 06382-84 and 06386 are .045-inch-thick, black, high performance, double-coated acrylic foam tapes. These OEM-approved tapes are designed for reliable attachment of a wid variety of automotive exterior and interior trim including body side moldings, claddings, rocker panel moldings, wheel flares, bumper trim and most other automotive trim.				
	3M Acrylic <i>Plus</i> Tape is OEM approved, utilizing breakthrough technology recently developed by 3M. With its unique, new high-performance adhesives on both sides, it offers improved adhesion over a variety of conditions, leading to reduced rework and warranty issues, offering the following key performance features:				
	<ul> <li>Superior adhesion build rate to automotive substrates</li> <li>More conformable core gives excellent wet-out (tape contact)</li> <li>Black, high-strength core maintains a thin, consistent bond line</li> <li>Easy liner release</li> </ul>				
	3M Acrylic <i>Plus</i> Tapes part numbers 06382, 06383, 06384 and 06386 are stronger, higher performing, higher stress handling products than other automotive attachment tapes. These tapes offer more robust performance to a wide variety of automotive substrates.				
Typical Applications	A & B pillar trim Luggage rack slats Door edge moldings				
	Emblems Wide body side molding.				
	Wheel flares Claddings Rocker panel moldings				
Product Construction	Easy-Release Liner VR-2 High Performance Acrylic Adhesive Black Acrylic Foam VR-1 High Performance Acrylic Adhesive				

Page 2

#### **Physical Properties**

Foam	Black acrylic	
Liner color	Red	
Thickness	.045 in. (1,14 mm)	
Package	Clam shell	

Ordering Information	Part Number	Color	Size	Rolls Per Box	Boxes Per Case
	06382	Black	1/2" x 20 yds (12,7 mm x 18,2 m)	1	12
	06383	Black	7/8" x 20 yds (22,2 mm x 18,2 m)	1	12
	06384	Black	1/2" x 5 yds (12,7 mm x 4,57 m)	1	12
	06386*	Black	1/4" x 20 yds (6,35 mm x 18,2 m)	1	12

\*Because of narrower width, 06386 is recommended for wheel flares or other less demanding applications.

Other Trim Attachment And Repair Products Please see your 3M catalog or consult your 3M representative for information about our complete line of automotive attachment tapes and adhesion promoter. Or you may visit us at www.3M.com/automotive, then click on "Product Catalog," then "3M<sup>™</sup> Tapes and Scotch<sup>®</sup> Tapes," and then "3M<sup>™</sup> Automotive Attachment Tapes."

**IMPORTANT NOTICE:** All statements and technical information in this literature are based on tests 3M believes are reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. 3M warrants that the products described in this literature will be free from defects in material or manufacture when shipped. 3M MAKES NO OTHER WARRANTIES REGARDING THESE PRODUCTS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Because there are many factors that can affect the use and performance of these products, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate these products to determine whether they are fit for a particular purpose, suitable for the user's method of application, and meet the user's performance specifications and expectations.

**Limitation of Remedies and Liability:** If any product described in this literature is defective, the exclusive remedy, at 3M's option, will be to refund the purchase price of or to replace the defective product. 3M IS NOT LIABLE FOR ANY OTHER LOSS OR DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THESE PRODUCTS REGARDLESS OF LEGAL THEORY.

#### **3M**

Automotive Aftermarket Division

3M Center, Building 223-6N-01 St. Paul, MN 55144-1000 www.3M.com/automotive

#### $\circledast$

Minimum 30% Post-Consumer Fiber Printed in U.S.A. © 3M 2002 75-3469-7534-7 2668-EMC C.I.C.

