



**STRIPPING DIMENSIONS**

Directive 2002/95/EC RoHS compliant

(b)

**NOTES:**

1. MATERIAL: COPPER ALLOY
2. PLATING:
  - ITEM 1: SEE TABLE
  - ITEM 2: GOLD FLASH over NICKEL
  - ITEM 3: NICKEL PLATED
3. CRIMPING: USE CRIMP TOOL 360X10409X  
WITH TOOL INSERT 360X20029X  
SELECTOR SETTINGS: 5 FOR AWG 12  
4 FOR AWG 14

(b)

PLATING ITEM 1	PART-NO.
GOLD FLASH over NICKEL	131A11029X
min. 30µin HARD GOLD over min. 50µin NICKEL	131C11029X
min. 50µin HARD GOLD over min. 50µin NICKEL	131J11029X

(b)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish: SEE NOTES				tolerance ISO 2768-m		dim. in mm		scale: 5:1			
								material: SEE NOTES			
				date		name		title: HIGH POWER CONTACT MALE CRIMP VERSION 20A D-SUB COMBINATION			
				drawn 23.03.98		Barcinski					
				appd. 23.03.98		Mickenbecker					
				norm							
				d-old				dwg no: 13K11D2A			
4 x b Ä3854 19.01.11 K.H.								DIN-A4			
a Origin										sh: 1	
rev. description date name										part no: SEE TABLE	

