imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



muRata Capacitor Data Sheet RCER71H332K0DBH03	*#" indicates a pack	age specification code.		
Recommended In Production Power AEC- 125 Anti- Deflecting So	Idening Flow OK Welding Ri	DHS REACH		
< List of part numbers with package codes > RCER71H332K0DBH03A				
Shape	Notes			
	· · ·	Meet LF(Lead Free)[%LF : Lead content is less than 1000 ppm.], HF(Halogen Free)		
	Refe	rences		
F od	Packaging	Specifications	Minimum quantity	
	А	Ammo pack taping type	2000	

Specifications

L size or outer diameter D (mm)

W size

T size

Lead spacing F

Lead diameter d

(in mm)

3.6 mm max.

3.5 mm max.

2.5 mm max.

2.5 +0.4/-0.2mm

0.5 ±0.05mm

Capacitance	3300pF±10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

