



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Zack Marker strip, flat - ZBF 4:SO/CMS - 0808639

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Zack Marker strip, flat, white, For terminal block width: 4 mm

The illustration shows versions  
ZBF 4- UNPRINTED, -  
LGS:CONSEC.NOS, -  
QR:CONSEC.NOS and -SO/  
CMS

### Key commercial data

Packing unit	1
Minimum order quantity	10
Catalog page	Page 432 (CL-2007)
GTIN	 4 017918 180225
Country of origin	GERMANY

### Technical data

#### General

Note	Please specify the required marking with order.
Note	10 identically marked strips make up one packing unit (PU).
Width (a)	4 mm
Color	white
Inflammability class according to UL 94	V2
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Ambient temperature (operation)	-40 °C ... 100 °C
Components	free from silicone and halogen
Pitch	4 mm
Material	PA
Number of individual labels	10
Pitch	4 mm

### Classifications

#### eclass

eCl@ss 4.0	24190208
------------	----------

## Zack Marker strip, flat - ZBF 4:SO/CMS - 0808639

### Classifications

#### eclass

eCl@ss 4.1	24190208
eCl@ss 5.0	27149103
eCl@ss 5.1	27149103
eCl@ss 6.0	27149103

#### etim

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761

#### unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410