

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



IPC with touch screen

Key commercial data

Packing unit	1 PCE
Custom tariff number	84714100
Country of origin	Taiwan

Technical data

Dimensions

External dimension, width	410 mm
External dimension, height	309 mm
External dimension, depth	96 mm
Installation dimension, width	386.6 mm
Installation dimension, height	285.6 mm

Display

Display	38.1 cm/15" TFT
Resolution	1024 x 768 Pixel (XGA)
Backlighting	CCFL
Display backlight MTBF	50000 h
Touch screen	Resistive industrial touch screen
Colors	16.2 million

Computer data

Processor	Intel [®] Core™2 Duo L7400 1,5 GHz
RAM	2 GB DDR SODIMM
Processor fan	Without fan
Mass storage	2.5" HDD, min. 250 Gbytes (SATA)
Graphics card	On-board graphics chip (AGP)



Technical data

Computer data

Interfaces	COM 1 (V.24 (RS-232)), 1x DVI-D, 1x VGA, 4x USB, 2x CompactFlash®
Network	2x Ethernet (10/100/1000 Mbps), RJ45
Operating systems	without
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)
Slots	without
Power supply unit	24 V DC ±20%

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	5 °C 55 °C (Configuration options can affect the operating temperature. See user manual for details)
Ambient temperature (storage/transport)	-40 °C 70 °C
Permissible humidity (operation)	5 % 95 % (no condensation)
Permissible humidity (storage/transport)	5 % 95 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Classifications

eCl@ss

eCl@ss 4.0	27360103
eCl@ss 4.1	27360103
eCl@ss 5.0	27360103
eCl@ss 5.1	27242401
eCl@ss 6.0	19200102
eCl@ss 7.0	19200102

ETIM

ETIM 3.0	EC001413
ETIM 4.0	EC001413
ETIM 5.0	EC001414

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404



Classifications

UNSPSC	
UNSPSC 13.2	43201404
Approvals	
Approvals	
Approvals	
UL Listed / cUL Listed / cULus Listed	
Ex Approvals	
Approvals submitted	
Approval details	
UL Listed (I)	
cUL Listed *	
cULus Listed [®]	

Accessories

Accessories

Mounting material



Accessories

Removable hard drive tray - HDD TRAY KIT - 2913185



Removable hard drive tray for Valueline IPC

Storage medium

Memory card - VL 512 MB CF - 2913154



CompactFlash® card, pluggable, 512 MB

Memory card - VL 1 GB CF - 2913155



CompactFlash® card, pluggable, 1 GB

Memory card - VL 2 GB CF - 2913156



CompactFlash® card, pluggable, 2 GB

Memory card - VL 4 GB CF - 2913157



CompactFlash® card, pluggable, 4 GB



Accessories

Memory card - VL 8 GB CF - 2913158



CompactFlash® card, pluggable, 8 GB

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com