



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




# SURFACE-MOUNT FUSES

## 2410 Very Fast-Acting Chip Fuses

The 2410 (6125mm) Wire-in-Air (WIA) SMD Fuse is suitable for secondary-level overcurrent protection applications.

These lead-free surface-mount devices offer increased reliability and avoid the risk of end caps falling off. Their straight wire element in air performs consistent fusing and cutting characteristics.



### BENEFITS

- Very fast acting at 200% overload current level
- Excellent inrush current withstand capability
- High reliability and resilience
- Strong arc suppression characteristics
- Copper terminal with nickel and tin plating

### FEATURES

- Halogen free, RoHS compliant and 100% lead free
- Copper or copper alloy composite fuse link
- Fiberglass enforced epoxy fuse body
- Wide range of current rating
- -55°C to +125°C operating temperature range (With de-rating)

### APPLICATIONS

- Industrial equipment
- LCD/PDP TV
- Backlight inverter
- Power supplier
- Telecom system
- Networking
- Game systems
- White goods
- Automotive

# Surface Mount Fuses

## 2410 Very Fast-Acting Chip Fuses


Table SFV1 — ClearTime Characteristics

% of Rated Current	ClearTime at 25°C	
100%	4 hrs (min)	—
200% (0.5A-10.0A)	0.01 s (min)	5 s (max)
200% (12.0A-20.0A)	0.01 s (min)	20 s (max)

Table SFV2 — Typical Electrical Characteristics, Dimensions and Recommended Pad Layout


### 2410 (6125 mm) Very Fast-Acting Fuse

Shape and Dimensions  
mm (in)



	A		B		C		D	
	Min	Max	Min	Max	Min	Max	Min	Max
mm	5.95	6.25	1.96	2.36	0.97	1.73	2.34	2.64
in	(0.234)	(0.246)	(0.077)	(0.093)	(0.038)	(0.068)	(0.092)	(0.104)

Recommended Pad Layout  
mm (Inch)




Part Number	Marking Code	Rated Current (A)	Interrupt Rating	Voltage Rating (V)		Nominal Cold DC Resistance (DCR) (Ω)*	Nominal I <sup>2</sup> t (A <sup>2</sup> s)
				AC	DC		
2410SFV0.50FM/125	C	0.5	<b>UL:</b> <b>0.5~2A</b> 100A @ 250V <sub>AC</sub> <b>2.5~8A</b> 50A @ 125V <sub>AC</sub> <b>0.5~8A</b> 50A @ 125V <sub>DC</sub> 300A @ 32V <sub>DC</sub>  <b>TUV:</b> <b>0.5A, 0.63A, 1A, 1.25A, 2A</b> 100A @ 250V <sub>AC</sub> 50A @ 125V <sub>DC</sub>  <b>CQC:</b> <b>0.5A, 1A, 2A</b> 100A @ 250V <sub>AC</sub> 50A @ 125V <sub>DC</sub>	250	125	0.231	0.1
2410SFV0.63FM/125	S	0.63		250	125	0.174	0.16
2410SFV0.75FM/125	D	0.75		250	125	0.148	0.23
2410SFV1.00FM/125	E	1		250	125	0.093	0.59
2410SFV1.25FM/125	F	1.25		250	125	0.07	0.96
2410SFV1.50FM/125	G	1.5		250	125	0.062	1.19
2410SFV2.00FM/125	I	2		250	125	0.042	2.75
2410SFV2.50FM/125	J	2.5		125	125	0.031	1.21
2410SFV3.00FM/125	K	3		125	125	0.0249	1.73
2410SFV3.15FM/125	V	3.15		125	125	0.0232	2.2
2410SFV3.50FM/125	L	3.5		125	125	0.022	2.5
2410SFV4.00FM/125	M	4	<b>UL:</b> 35A @ 125V <sub>AC</sub> 50A @ 125V <sub>DC</sub> 300A @ 32V <sub>DC</sub>	125	125	0.0172	4.1
2410SFV5.00FM/125	N	5		125	125	0.0143	5.9
2410SFV6.30FM/125	O	6.3		125	125	0.01	12.5
2410SFV7.00FM/125	P	7		125	125	0.0094	14.2
2410SFV8.00FM/125	R	8		125	125	0.0086	20.3
2410SFV10.0FM/125	Q	10		125	125	0.0066	29.2
2410SFV12.0FM/065	X	12		65	65	0.0053	49.2
2410SFV15.0FM/065	Y	15		65	65	0.0038	102.5
2410SFV20.0FM/065	Z	20		65	65	0.0034	126.2
2410SFV20.0FM/065	Z	20		65	65	0.0034	126.2

\* Measured at ≤10% of rated current and 25°C ambient



Surface Mount Fuses  
2410 Very Fast-Acting Chip Fuses

Figures SFV1-SFV2 — Family Performance Curves



## Surface Mount Fuses

### 2410 Very Fast-Acting Chip Fuses

#### **Notice:**

Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.