

Ferrule - A 35 -40 - 3241239

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ferrule, sleeve length: 40 mm, length: 40 mm, color: silver

Why buy this product

- The ferrules without plastic sleeve are made from soft tin-plated electrolytic copper

Key Commercial Data

Packing unit	100 STK
GTIN	 4 046356 908122
GTIN	4046356908122

Technical data

Dimensions

Length (b)	40 mm
Maximum stripping length	40 mm
Sleeve length	40 mm
Inner dimension of the insulating collar (d)	11 mm
Ferrule diameter	8.2 mm
Sleeve wall thickness	0.2 mm

Ambient conditions

Short-term temperature	120 °C
Max. permanent temperature	105 °C

General

Note	These ferrules are not included in DIN 46228-1: 1992-08
Color	silver
Material	CU-DHP
Coating	tin-plated (galvanic)

Ferrule - A 35 -40 - 3241239

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>