

Specification Sheet

Part Number: 596-00232



Solar Label, WARNING ELECTRICAL SHOCK HAZARD...DC VOLTAGE, 3.75" x 2.5", VL, Red, 50/roll

Article Number	596-00232
Type	WESHLBLDC
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">• Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.• Supplied with an aggressive adhesive to ensure long life.• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.• Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
Quantity Per	roll

Product Description

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, WARNING ELECTRICAL SHOCK HAZARD...DC VOLTAGE, 3.75" x 2.5", VL, Red, 50/roll

Global Part Name

WESHLBLDC-443/552-RD

Technical Description

Pre-Printed Solar Label, "WARNING - ELECTRICAL SHOCK HAZARD W/DC", 3.75" X 2.5", Red

Width W (Imperial)

3.75

Width W (Metric)

95.25

Thickness T (Metric)

64.0

Height H (Imperial)

2.50

Height H (Metric)

63.50

Material

Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate

Material Shortcut

443/552

Adhesive

Acrylic

Halogen free

No

Adhesive Operating Temperature

-40°F to +176°F (-40°C to +80°C)

Operating Temperature (Metric)

-40°F to +174°F (-40°C to +79°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 969
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521
Weight (Imperial)	3.2