



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



| | |
|--|--|
| Material | High Conductivity Seamless Copper Tube |
| Plating | Electro-Tin |
| Wire Size | 350 SIR/FLEX |
| Wire Type | Stranded Copper: Class G, H, I, K, M, Locomotive |
| Wire Strip Length | 2-9/16 in. |
| Stud Size | 1/4 in. |
| UL Listed Wire Connector | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating | 90 ° C |
| C.S.A Certified Wire Connector | Yes |
| Panduit Color Code on Barrel | BLUE |
| Panduit Die Index No. on Barrel | P76 |
| Alternate Industry Die Index No. () on Barrel | (19) |




Technical drawing of a Panduit 350 STR/FLEX LCX350-14BH connector. The drawing shows a side view of the connector with dimensions: overall height 1.54±.04, mounting hole diameter .25±.04, distance between mounting holes .75±.02, and a .34 R Ref fillet radius. The connector is labeled 'PANDUIT 350 STR/FLEX LCX350-14BH'. A note indicates '(2) PLS' for the mounting holes.



Technical drawing of a wire inspection window. The drawing shows a cross-section of a rectangular window with a beveled wire entry. The dimensions are as follows:

- Beveled wire entry: $1.06 \pm .01$
- Wire inspection window: $.84 \pm .01$
- Wire inspection window: $2.50 \pm .04$
- Wire inspection window: 3.16 REF
- Wire inspection window: $45^\circ \pm 5^\circ$
- Wire inspection window: $.22 \pm .01$
- Wire inspection window: 3.81 REF

| | | | | | | | |
|------------|-------------|-----------|------------|--------------------|------------|--|--|
| | | | | | |  PANDUIT CORP. TINLEY PARK, ILLINOIS | |
| | | | | | | LC C X350-14BH-6 Copper Lug - Two-Hole, Long Flex Barrel with Window, 45° Angle Tongue | |
| 00 | 6/03 | SAC | SAC | RELEASED | 10850 | | |
| REV | DATE | BY | CHK | DESCRIPTION | ECN | SCALE N/A | DRAWING NO / CAD FILE LC C X350-14BH-C UST |