



ROHS compliant

Scale	Free
TOLERANCE	
.X	±0.30
.XX	±0.20
.XXX	±0.10
DIM	TOL
X.°	±5°
Angle	TOL
UNIT	mm

Id.	Modification	Date	Name
①	Change part number	15.12.2014	Jessy
②	Drawn	07.06.2013	Winnie

Date	Name
07.06.2013	Winnie
07.06.2013	Winnie



Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace	SHEET
	① A-USBPA-2	ASS 5782 CO		rev01

- NOTES:**
- Material:
 - Housing: PBT+30%GF UL94V-0, Color White
 - Shell: SPCC
 - Contact :Brass
 - FINISH:
 - Contact Area: Selective30u"Au
 - Solder Area:Tin Plated
 - MECHANICAL:
 - Mating Force:3.57kgf Max.
 - Umating Force:1.02kgf Min
 - Durability:1500 cycles Min
 - ELECTRICAL:
 - Current Rating:1.5A
 - Dielectric Strength:500V AC FOR 1 MINUTE
 - Contact Resistance:30mΩ Max
 - Insulation Resistance:1000 MΩ Min
 - Operating temperature: -55°C TO +85°C
 - PACKIING: PE Bag

1	2	3	4	5	6	7
H	G	F	E	D	C	B
1	2	3	4	5	6	7
H	G	F	E	D	C	B