

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









General ordering data

Order No. 1805720000

Part designation SFC 1/30 NEUTRAL BL

Version Conductor markers, L x W: 30 x 4 mm, Polyamide,

Blue

EAN 4032248273454

Qty. 150 pc(s).

| Markings   |                             |
|--|-----------------------------|
| Cadmium  | no                          |
| Can be labelled with thermal transfer printers               | No                          |
| Can be printed with plotter                                  | Yes                         |
| Can be written with dot-matrix printer                       | No                          |
| Can be written with laser printer                            | No                          |
| Conductor O.D., max.   | 3.5 mm                      |
| Conductor O.D., min.   | 2 mm                        |
| Conductor cross-section, max.                                | 2.5 mm <sup>2</sup>         |
| Conductor cross-section, max.  Conductor cross-section, min. | 0.75 mm <sup>2</sup>        |
| Function   | Conductor and cable markers |
| Halogen  | no                          |
| Height   | 5 mm                        |
| Insulation cross-section, max.                               | 3.5 mm                      |
|  | 3.5 mm                      |
| Length   |                             |
| Material   | Polyamide                   |
| Material colour  | Blue                        |
| Material colour according to resistance code                 | 6                           |
| Max. temperature, continuous                                 | 100 °C                      |
| Min. temperature, continuous                                 | -40 °C                      |
| Pin can be written (STI)                                     | Yes                         |
| PrintJet   | Yes                         |
| Printed characters   | without                     |
| Silicone   | no                          |
| Speed marking laser  | Yes                         |
| Type of printing   | Neutral                     |
| UL 94 flammability class                                     | V2                          |



| Markings             |                     |  |
|----------------------|---------------------|--|
| Width                |                     | 4 mm   |
| Approvals            |                     |  |
| Approvals institutes |                     | n.a.   |
| Classification       |                     |  |
| ETIM 2.0             |                     | EC001530   |
| ETIM 3.0             |                     | EC001530   |
| eClass 4.1           |                     | 24-19-02-19  |
| eClass 5.0           |                     | 27-14-91-03  |
| eClass 5.1           |                     | 27-14-91-03  |
| Similar prod         | ucts                |  |
| Order No.            |                     |  |
| 1813270000           | SFC 0/30 NEUTRAL BL | Conductor markers, L x W: 30 x 4 mm, Polyamide, Blue |

1805820000 SFC 2/30 NEUTRAL BL

SFC 3/30 MC NE BL

1025340000

Conductor markers, L x W: 30 x 4 mm, Polyamide, Blue

Conductor markers, L x W: 30 x 4 mm, Polyamide, Blue