



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PACKAGE DIMENSIONS



SCHEMATIC



NOTES:

1. Dimensions for all drawings are in inches.
2. Tolerance of $\pm .010$ on all non-nominal dimensions unless otherwise specified.

DESCRIPTION

The QRE00034 reflective object sensor consists of an infrared emitting diode and an NPN phototransistor mounted side by side on a converging optical axis in a black housing. The phototransistor responds to radiation from the emitting diode only when a reflective object passes in its field of view.

FEATURES

- Phototransistor output
- No contact surface sensing
- Daylight filter on the sensor
- Emitter $\lambda = 940$ nm

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise specified)

| Parameter | Symbol | Rating | Units |
|---|--------------------|----------------|-------|
| Operating Temperature | T _{OPR} | -40 to +85 | °C |
| Storage Temperature | T _{STG} | -40 to +85 | °C |
| Soldering Temperature (Iron) ^(2,3,4) | T _{SOL-I} | 240 for 5 sec | °C |
| Soldering Temperature (Flow) ^(2,3) | T _{SOL-F} | 260 for 10 sec | °C |
| EMITTER | | | |
| Continuous Forward Current | I _F | 50 | mA |
| Reverse Voltage | V _R | 5 | V |
| Peak Forward Current | I _{FP} | 1 | A |
| Power Dissipation ⁽¹⁾ | P _D | 100 | mW |
| SENSOR | | | |
| Collector-Emitter Voltage | V _{CEO} | 30 | V |
| Power Dissipation ⁽¹⁾ | P _D | 100 | mW |

ELECTRICAL / OPTICAL CHARACTERISTICS (T_A = 25°C)

| PARAMETER | TEST CONDITIONS | SYMBOL | MIN | TYP | MAX | UNITS |
|--------------------------------------|---|-----------------------|------|-----|------|-------|
| EMITTER | | | | | | |
| Forward Voltage | I _F = 20 mA | V _F | — | — | 1.7 | V |
| Reverse Current | V _R = 5 V | I _R | — | — | 100 | μA |
| Peak Emission Wavelength | I _F = 20 mA | λ _{PE} | — | 940 | — | nm |
| SENSOR | | | | | | |
| Dark Current | V _{CE} = 10 V, I _F = 0 mA | I _D | — | — | 100 | nA |
| Peak Sensitivity Wavelength | V _{CE} = 5 V | λ _{PS} | — | 880 | — | nm |
| COUPLED | | | | | | |
| Collector Current | I _F = 20 mA, V _{CE} = 10 V ^(6,7) | I _{C(ON)} | 0.16 | — | 2.00 | mA |
| Collector Emitter Saturation Voltage | I _F = 20 mA, I _C = 0.5 mA | V _{CE (SAT)} | — | — | 0.4 | V |
| Rise Time | V _{CE} = 5 V, R _L = 100 Ω | t _r | — | 10 | — | μs |
| Fall Time | I _{C(ON)} = 5 mA | t _f | — | 50 | — | μs |

NOTES

- Derate power dissipation linearly 1.33 mW/°C above 25°C.
- RMA flux is recommended.
- Methanol or isopropyl alcohols are recommended as cleaning agents.
- Soldering iron tip at 1/16" (1.6mm) from housing.
- Pulse conditions: t_p = 10 μs; T = 1 ms.
- Measured as an Eastman Kodak neutral white test card with 90% diffused reflectance as a reflecting surface.
- 0.160" (4 mm) distance from sensor face to reflector surface.

TYPICAL PERFORMANCE CURVES

Fig. 1 Normalized Collector Current vs. Distance




Fig. 2 Forward Current vs. Forward Voltage




Fig. 3 Normalized Collector Current vs. Angle Deviation




Fig. 4 Collector Current vs. Forward Current




Fig. 5 Normalized Collector Current vs. Ambient Temperature




Fig. 6 Rise and Fall Time vs. Collector Current




Fig. 7 Collector Current vs. Collector to Emitter Voltage




Fig. 8 Collector Emitter Dark Current vs. Forward Current




Fig. 9 Forward Voltage vs. Ambient Temperature




Fig. 10 Normalized Collector Current vs. Distance d_2




Fig. 11 Normalized Collector Current vs. Distance d_2






Fig. 12 Normalized Collector Current vs. Distance d_2



ANTISTATIC PLASTIC TUBE PACKING (50 PCS PER TUBE)



NOTES

1. Dimensions: All dimensions are in mm.
2. Color: Clear (Transparent).
3. Antistatic resistivity level: $10^5 - 10^{12}$ Ohm/sq.
4. Tolerance: ± 0.25 inches, unless otherwise specified.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.