



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RFID HD RooTenna® 10 X 10 Die-Cast Enclosure RFID Antennas




DCE ENCLOSURE OFFERS SIX OPTIONS OF INTEGRATED RFID ANTENNAS COVERING 860-960 MHz

The RFID HD RooTenna® from Laird Technologies is an innovative antenna system that gives the operator ultimate system flexibility. The Radome is UV resistant ASA plastic, the hardware is stainless steel, and the mounting plate inside for adding electronics is removable and customizable by the user.

The die-cast enclosure can be pole or wall mounted. A heavy duty tilt bracket is available for those installations requiring up or down tilt. Eleven (11) engineered knockouts are provided; nine sized for N connectors, and two sized for a cable feed through.

This series of antennas is available with a choice of six different circularly polarized UHF antennas integrated into the Radome cover. These antennas cover the standard 902-928 MHz, 865-868 MHz RFID frequencies, as well as a wide band version that covers 865-960 MHz. All are available in a choice of RH and LH circular polarization. These antennas feature very low VSWR, axial ratio, and a fixed SMA connector.

ANTENNA PATTERN



865 MHz 5.46 dBi Linear A

FEATURES

- 11 engineered knockouts
- IP 67 Rated
- Rugged and weatherproof
- Hinged cover for easy maintenance
- Choice of six high-performance, circularly-polarized antennas

MARKETS

- Outdoors
- Loading docks
- Warehouses
- Mast mounted
- Side of building
- Industrial / wet locations

SPECIFICATIONS	DCE9028PR / L	DCE8658PR / L	DCE8658WPR / L
Frequency:	902-928 MHz	865-870 MHz	865-960 MHz
Gain:	9 dBic	8.5 dBic	8.5 dBic
3 dB Beamwidth	70° x 70°	70° x 70°	65° x 65°
Polarization:	Right or Left Hand Circular	Right or Left Hand Circular	Right or Left Hand Circular
VSWR:	<1.3:1	<1.5:1	<1.40:1
Front-to-Back Ratio	20 dB	18dB	18dB
Axial Ratio	1 dB	1 dB	1 dB
RF Connector:	SMA (female)	SMA (female)	SMA (female)
Power Rating:	10 W	10 W	3 W
Radome:	ASA	ASA	ASA
Dimensions:	12.5" x 10.4" x 3.9"	12.5" x 10.4" x 3.9"	12.5" x 10.4" x 3.9"
Weight:	2.4 kg	2.4 kg	2.4 kg
Operational Temperature:	-30°C to +75°C	-30°C to +75°C	-30°C to +75°C
Mount Style:	Wall / Mast / Tilt	Wall / Mast / Tilt	Wall / Mast / Tilt

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-RFID-DCE 0115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.