

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

## Chip EMIFIL® LC Combined Monolithic

NFL15ST□□7X0J3□

## Reference Specification

## 1. Scope

This reference specification applies to Chip EMIFIL® LC Combined Monolithic Type NFL15ST Series.

## 2. Part Numbering

$\frac{\text{NF}}{\text{Product ID}}$ 
 $\frac{\text{L}}{\text{Structure}}$ 
 $\frac{15}{\text{Dimension (L×W)}}$ 
 $\frac{\text{ST}}{\text{Features}}$ 
 $\frac{157}{\text{Cut-off Frequency}}$ 
 $\frac{\text{X}}{\text{Characteristics}}$ 
 $\frac{0\text{J}}{\text{Rated Voltage}}$ 
 $\frac{3}{\text{Electrode}}$ 
 $\frac{\text{D}}{\text{Packaging Code (D: Taping / B: Bulk)}}$

## 3. Rating

Customer Part Number	MURATA Part Number	Cut-off Frequency [MHz]	Insertion Loss (I.L.)(dB)		DC Resistance [Ω]	Rated Current [mA(DC)]	Insulation Resistance [MΩ min.]	Rated Voltage [V(DC)]	Withstanding Voltage [V(DC)]
	NFL15ST157X0J3D	150	6 max. (0 to 150MHz)	25 min. (400 to 1000MHz)	20±30%	50	1000	6.3	18.9
	NFL15ST157X0J3B								
	NFL15ST207X0J3D	200	6 max. (0 to 200MHz)	25 min. (600 to 1000MHz)	18±30%				
	NFL15ST207X0J3B								
	NFL15ST307X0J3D	300	6 max. (0 to 300MHz)	25 min. (800 to 1000MHz)	17±30%				
	NFL15ST307X0J3B								
	NFL15ST507X0J3D	500	6 max. (0 to 500MHz)	25 min. (1000MHz)	14±30%				
	NFL15ST507X0J3B								

<Capacitance> NFL15ST157X0J3□: 22pF (typ.)

NFL15ST207X0J3□: 17pF (typ.)

NFL15ST307X0J3□: 12pF (typ.)

NFL15ST507X0J3□: 7pF (typ.)

<Inductance> NFL15ST157X0J3□: 115nH (typ.)

NFL15ST207X0J3□: 105nH (typ.)

NFL15ST307X0J3□: 95nH (typ.)

NFL15ST507X0J3□: 60nH (typ.)

- Operating Temperature: -40°C to +85°C
- Storage Temperature: -40°C to +85°C

## 4. Standard Testing Condition

< Unless otherwise specified >

Temperature: Ordinary Temp. / 15 °C to 35 °C

Humidity: Ordinary Humidity / 25 %(RH) to 85 %(RH)

< In case of doubt >


Temperature: 20 °C ± 2 °C

Humidity: 60 %(RH) to 70 %(RH)


Atmospheric pressure: 86 kPa to 106 kPa

## 5. Style and Dimensions


(Top view)



(Side View)




(Bottom View)



: Polarity Marking  
 : Electrode (in mm)

## ■ Equivalent Circuits




■ Unit Mass(Typical value)  
0.5mg

■ **NC (Non-Contact) Terminal**

Don't connect NC terminal with any signal lines/GND lines on the circuit board.

■ **Insertion Loss Characteristics (I.L.) (Typ.)** (50Ω system)



**6. Marking**

Polarity marking is on the upper surface of a product.



**7. Electrical Performance**

No.	Item	Specification	Test Method
7.1	Insertion Loss (I.L.)	Meet item 3.	<p>*Method of measurement based on MIL-STD-220                      Insertion Loss = 20 log (E<sub>0</sub> / E<sub>1</sub>)                      E<sub>0</sub> : Level without FILTER (short)                      E<sub>1</sub> : Level with FILTER</p>
7.2	DC Resistance (Rdc)		Measured with 10mA max.
7.3	Insulation Resistance(I.R.)		Measured between terminal ①-③. (ref. Item5)
7.4	Withstanding Voltage	Products shall not be damaged.	· Voltage : Rated Voltage · Time : 1 minutes max. · Test Voltage : Rated Voltage × 300% · Time : 1 to 5s · Charge Current : 50 mA max.

**8. Mechanical Performance**

No.	Item	Specification	Test Method
8.1	Appearance and Dimensions	Meet item 5.	Visual Inspection and measured with Slide Calipers.
8.2	Solderability	Electrodes shall be at least 90% covered with new solder coating.	· Flux : Ethanol solution of rosin, 25(wt)% · Pre-heat : 150 ± 10°C, 60 to 90s · Solder : Sn-3.0Ag-0.5Cu · Solder Temperature : 240 ± 3°C · Immersion Time : 3±1 s · Immersion and emersion rates : 25mm / s

# Reference Only

No.	Item	Specification	Test Method								
8.3	Resistance to soldering heat	Meet Table 1.  <table border="1" style="margin-left: 20px; border-collapse: collapse;"> <caption>Table 1</caption> <tr> <td style="padding: 2px;">Appearance</td> <td style="padding: 2px;">No damaged</td> </tr> <tr> <td style="padding: 2px;">Cap. Change</td> <td style="padding: 2px;">Within <math>\pm 10\%</math></td> </tr> <tr> <td style="padding: 2px;">L Change</td> <td style="padding: 2px;">Within <math>\pm 10\%</math></td> </tr> <tr> <td style="padding: 2px;">I.R.</td> <td style="padding: 2px;">Meet item 3</td> </tr> </table>	Appearance	No damaged	Cap. Change	Within $\pm 10\%$	L Change	Within $\pm 10\%$	I.R.	Meet item 3	<ul style="list-style-type: none"> <li>· Flux : Ethanol solution of rosin, 25(wt)%</li> <li>· Pre-heat : <math>150 \pm 10^\circ\text{C}</math>, 60 to 90s</li> <li>· Solder : Sn-3.0Ag-0.5Cu</li> <li>· Solder Temperature : <math>270 \pm 5^\circ\text{C}</math></li> <li>· Immersion Time : <math>10 \pm 1</math> s</li> <li>· Immersion and emersion rates : 25mm / s</li> <li>· Then measured after exposure in the room condition for <math>24 \pm 2</math> hours.</li> </ul>
Appearance	No damaged										
Cap. Change	Within $\pm 10\%$										
L Change	Within $\pm 10\%$										
I.R.	Meet item 3										
8.4	Bending Strength	Meet Table 1.	<p>It shall be soldered on the glass-epoxy substrate (<math>t = 1.0\text{mm}</math>).</p> <ul style="list-style-type: none"> <li>· Deflection : 2 mm</li> <li>· Keeping Time : 30 s Pressure jig</li> </ul>  <p style="text-align: right;">Deflection Product (in mm)</p>								
8.5	Drop	Products shall be no failure after tested.	<p>It shall be dropped on concrete or steel board.</p> <ul style="list-style-type: none"> <li>· Method : Free fall</li> <li>· Height : 1m</li> <li>· Attitude from which the product is dropped : 3 directions</li> <li>· The Number of Time : 3 times for each direction (Total 9 times)</li> </ul>								
8.6	Bonding Strength	The electrodes shall be no failure after tested.	<p>It shall be soldered on the glass-epoxy substrate.</p> <ul style="list-style-type: none"> <li>· Applying Force (F) : 5 N</li> <li>· Applying Time : 30 s</li> </ul>  <p style="text-align: right;">(in mm)</p>								
8.7	Vibration	Meet Table 1.	<p>It shall be soldered on the glass-epoxy substrate.</p> <ul style="list-style-type: none"> <li>· Oscillation Frequency : 10 to 2000 to 10Hz for 15 min</li> <li>· Total amplitude 3.0mm or Acceleration amplitude <math>196\text{m/s}^2</math> whichever is smaller.</li> <li>· Time: A period of 2 hours in each of 3 mutually perpendicular directions. (Total 6 hours)</li> </ul>								

## 9. Environment Performance


It shall be soldered on the glass-epoxy substrate.

No.	Item	Specification	Test Method
9.1	Temperature Cycling	Meet Table 1.	<ul style="list-style-type: none"> <li>· 1 Cycle <ul style="list-style-type: none"> <li>1 step : <math>-40 \pm 0_3^\circ\text{C} / 30 \pm 3_0</math> min</li> <li>2 step : Room Temperature / within 3 min</li> <li>3 step : <math>+85 \pm 3_0^\circ\text{C} / 30 \pm 3_0</math> min</li> <li>4 step : Room Temperature / within 3 min</li> </ul> </li> <li>· Total of 100 cycles</li> <li>· Then measured after exposure in the room condition for <math>24 \pm 2</math> hours.</li> </ul>
9.2	Humidity		<ul style="list-style-type: none"> <li>· Temperature : <math>40 \pm 2^\circ\text{C}</math></li> <li>· Humidity : 90 to 95%(RH)</li> <li>· Time : <math>1000 \pm 24_0</math> hours</li> <li>· Then measured after exposure in the room condition for <math>24 \pm 2</math> hours.</li> </ul>

No.	Item	Specification	Test Method
9.3	Heat Life	Meet Table 1.	<ul style="list-style-type: none"> <li>· Temperature : <math>85 \pm 2</math> °C</li> <li>· Test Voltage : Rated Voltage <math>\times</math> 200%</li> <li>· Charge Current : 50 mA max.</li> <li>· Time : <math>1000 \pm {}^{48}_0</math> hours</li> <li>· Then measured after exposure in the room condition for <math>24 \pm 2</math> hours.</li> </ul>

## 10. Specification of Packaging

### 10.1. Appearance and Dimensions (8mm-wide paper tape)



### 10.2. Specification of Taping

(1) Packing quantity (standard quantity)

10,000 pcs. / reel

(2) Packing Method

Products shall be packaged in the cavity of the base tape and sealed by cover tape.

(3) Sprocket Hole

The sprocket holes are to the right as the tape is pulled toward the user.

(4) Base tape and Cover tape

The base tape and cover tape have no spliced point.

(5) Cavity

There shall not be burr in the cavity.

(6) Missing components number

Missing components number within 0.1% of the number per reel or 1 pc., whichever is greater, and are not continuous. The specified quantity per reel is kept.


### 10.3. Pull Strength of Cover tape

Cover tape	5N min.
------------	---------

### 10.4. Peeling off force of Cover tape


0.1N to 0.6N (minimum value is typical)

Speed of Peeling off : 300 mm / min



### 10.5. Dimensions of Leader-tape, Trailer and Reel

There shall be leader-tape (cover tape and empty tape) and trailer-tape (empty tape) as follows.





**12.2. Connection to NC(Non-Contact) Terminal**

Please don't connect NC terminal with any signal lines or GND lines on the circuit board.

When NC terminal is connected to GND, it causes fuming or partial dispersion because input or output signal terminals short-circuit to ground.

**12.3. Limitation of Applications**

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.

- (1) Aircraft equipment (2) Aerospace equipment (3) Undersea equipment (4) Power plant control equipment  
 (5) Medical equipment (6) Transportation equipment(automobiles, trains, ships, etc.) (7) Traffic signal equipment  
 (8) Disaster prevention / crime prevention equipment (9) Data-processing equipment  
 (10) Applications of similar complexity or with reliability requirements comparable to the applications listed in the above

**13. Notice**

Products can only be soldered with reflow.

This product is designed for solder mounting.

Please consult us in advance for applying other mounting method such as conductive adhesive.

**13.1. Flux and Solder**

Flux	Use rosin-based flux, Do not use highly acidic flux (with chlorine content exceeding 0.2(wt)%). Do not use water-soluble flux.
Solder	Use Sn-3.0Ag-0.5Cu solder

Other flux (except above) Please contact us for details, then use.

**13.2. Note for Assembling**

< Thermal Shock >

Pre-heating should be in such a way that the temperature difference between solder and products surface is limited to 100°C max. Also cooling into solvent after soldering should be in such a way that the temperature difference is limited to 100°C max.

<NC (Non-Contact) Terminal>


Please solder the NC terminal on floated pattern, in order to secure the fixing strength of the part and to prevent displacement of the part during reflow soldering.

**13.3. Attention Regarding P.C.B. Bending**

The following shall be considered when designing P.C.B.'s and laying out products.


- (1) P.C.B. shall be designed so that products are not subject to the mechanical stress for board warpage.

[Products direction]



Products shall be located in the sideways direction (Length: $a < b$ ) to the mechanical stress.

- (2) Products location on P.C.B. near seam for separation.



Products (A,B,C,D) shall be located carefully so that products are not subject to the mechanical stress due to warping the board.

Because they may be subjected the mechanical stress in order of  $A > C > B \cong D$ .

**13.4. Pre-heating Temperature**


Soldering shall be handled so that the difference between pre-heating temperature and solder temperature shall be limited to 100°C max. to avoid the heat stress for the products.

### 13.5. Reflow Soldering

#### 1) Soldering paste printing for reflow

- Standard thickness of solder paste: 100µm to 150µm.
- Use the solder paste printing pattern of the right pattern.
- For the resist and copper foil pattern, use standard land dimensions.


- Standard printing pattern of solder paste.



#### 2) Soldering Conditions

Standard soldering profile and the limit soldering profile is as follows.

The excessive limit soldering conditions may cause leaching of the electrode and / or resulting in the deterioration of product quality.



	Standard Profile	Limit Profile
Pre-heating	150°C ~ 180°C , 90s ± 30s	
Heating	above 220°C , 30s ~ 60s	above 230°C , 60s max.
Peak temperature	245°C ± 3°C	260°C , 10s
Cycle of reflow	2 times	2 times

### 13.6. Reworking with Soldering iron


The following conditions shall be strictly followed when using a soldering iron.

- Pre-heating : 150°C, 1 min
- Tip temperature : 350°C max.
- Soldering time : 3(+1,-0) s
- Soldering iron output : 30W max.
- Tip diameter : φ 3mm max.
- Times : 2times max.

Note: Do not directly touch the products with the tip of the soldering iron in order to prevent the crack on the ceramic material due to the thermal shock.

### 13.7. Solder Volume

Solder shall be used not to be exceeded as shown below.



Accordingly increasing the solder volume, the mechanical stress to product is also increased. Excessive solder volume may cause the failure of mechanical or electrical performance.

**13.8. Cleaning Conditions**

Products shall be cleaned on the following conditions.

- (1) Cleaning temperature shall be limited to 60°C max. (40°C max. for Isopropyl alcohol (IPA))
- (2) Ultrasonic cleaning shall comply with the following conditions, with avoiding the resonance phenomenon at the mounted products and P.C.B.
  - Power: 20W / l max.
  - Frequency: 28kHz to 40kHz
  - Time: 5 minutes max.
- (3) Cleaner
  1. Cleaner
    - Isopropyl alcohol (IPA)
  2. Aqueous agent
    - PINE ALPHA ST-100S
- (4) There shall be no residual flux and residual cleaner after cleaning.
 

In the case of using aqueous agent, products shall be dried completely after rinse with de-ionized water in order to remove the cleaner.
- (5) Other cleaning
 

Please contact us.

**13.9. Operating Environment**

Do not use this product under the following environmental conditions, on deterioration of the performance, such as insulation resistance may result from the use.

- (1) in the corrodible atmosphere (acidic gases, alkaline gases, chlorine, sulfur gases, organic gases and etc.)
- (2) in the atmosphere where liquid such as organic solvent, may splash on the products.
- (3) in the atmosphere where the temperature / humidity changes rapidly and it is easy to dew.

**13.10. Resin coating**

The capacitance and inductance value may change and/or it may affect on the product's performance due to high cure-stress of resin to be used for coating / molding products. So please pay your careful attention when you select resin. In prior to use, please make the reliability evaluation with the product mounted in your application set.

**13.11. Handling of a substrate**

After mounting products on a substrate, do not apply any stress to the product caused by bending or twisting to the substrate when cropping the substrate, inserting and removing a connector from the substrate or tightening screw to the substrate.

Excessive mechanical stress may cause cracking in the product.

**13.12. Storage condition****(1) Storage period**

Use the products within 12 months after delivered.

Solderability should be checked if this period is exceeded.

**(2) Storage environment condition**

· Products should be stored in the warehouse on the following conditions.

Temperature : -10 to +40°C

Humidity : 15 to 85% relative humidity

No rapid change on temperature and humidity

- Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solderability.
- Products should be stored on the palette for the prevention of the influence from humidity, dust and so on.
- Products should be stored in the warehouse without heat shock, vibration, direct sunlight and so on.
- Products should be stored under the airtight packaged condition.

**(3) Delivery**

Care should be taken when transporting or handling product to avoid excessive vibration or mechanical shock.

**14. ⚠ Notes**

- (1) Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
- (2) You are requested not to use our product deviating from the reference specifications.
- (3) The contents of this reference specification are subject to change without advance notice. Please approve our product specifications or transact the approval sheet for product specifications before ordering.