

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







CHIP COIL (CHIP INDUCTORS) LQH5BPN□□□□38□ REFERENCE SPECIFICATION

1.Scope

This reference specification applies to LQH5BP_38 series, Chip coil (Chip Inductors).

2.Part Numbering

(ex)LQH5BPN220M38LProduct IDStructureDimension (L×W)ApplicationsCategoryInductanceToleranceDimension (T)Packaging (T)andCharacteristics(T)L: Φ180Taping (T)

3.Rating

Operating Temperature Range.

(Ambient temperature; Self-temperature rise is not included) -40 to +85°C (Product temperature; Self- temperature rise is included) -40 to +125°C

•Storage Temperature Range. -40 to +85°C

<u> </u>	mperature Kange40 to	Inductance		DC Resistance		Self	*3Rated Current(mA)	
Customer Part Number	Murata Part Number	(µH)	Tolerance (%)	(Ω)	Tolerance (%)	Resonant Frequency (MHz min)	*1 (Based on inductance change)	*2 (Based on temperature rise)
	LQH5BPN1R0N38L	1.0		0.012	54	7000	4600	
	LQH5BPN1R0N38K	1.0				54	7000	4000
	LQH5BPN1R5N38L	1.5		0.014		50	6500	4500
	LQH5BPN1R5N38K	1.5		0.014		50	0300	4500
	LQH5BPN2R2N38L	2.2	N:±30	0.016		45	5000	4300
	LQH5BPN2R2N38K	2.2	IN.±30	0.016		40	5000	4300
	LQH5BPN3R3N38L	3.3		0.021		25	4000	4000
	LQH5BPN3R3N38K	3.3		0.021		25	4000	4000
	LQH5BPN4R7N38L	4.7		0.026		17	0500	3800
	LQH5BPN4R7N38K	4.7	'			17	3500	3000
	LQH5BPN6R8M38L	6.8		0.039		15	3000	3000
	LQH5BPN6R8M38K	0.0		0.039	0.056 ±20%	15		
	LQH5BPN100M38L	10		0.056		13	2600	2200
	LQH5BPN100M38K	10		0.056		13	2000	2200
	LQH5BPN150M38L	15		0.08		10	1800	1900
	LQH5BPN150M38K	13		0.00			1000	1900
	LQH5BPN220M38L	22		0.11	1	8.0	1600	1500
	LQH5BPN220M38K	22		0.11		0.0	1000	1500
	LQH5BPN330M38L	33	M:±20	0.15		6.5	1300	1300
	LQH5BPN330M38K	33	IVI.±ZU			0.5	1300	1300
	LQH5BPN470M38L	47		0.22		6.0	1100	1100
	LQH5BPN470M38K	77		0.22		6.0	1100	1100
	LQH5BPN680M38L	68		0.33		5.0	900	030
	LQH5BPN680M38K			0.33		4.0	750	930 740
	LQH5BPN101M38L							
	LQH5BPN101M38K							
	LQH5BPN151M38L	150		0.69		3.5	650	630
	LQH5BPN151M38K	130		0.00		3.0	000	030

^{*1} When applied Rated current to the Products, Inductance will be within ±30% of initial inductance value range.

^{*2} When applied Rated current to the Products ,temperature rise caused by self-generated heat shall be limited to 40°C max.(Ambient temperature 85°C).

^{*3} Keep the temperature (ambient temperature plus self-generation of heat) under 125°C.

Reference Only

4. Testing Conditions


<Unless otherwise specified>

Temperature : Ordinary Temperature (15 to 35°C) Humidity : Ordinary Humidity (25 to 85 %(RH)) <In case of doubt>


Temperature : 20 ± 2°C Humidity : 60 to 70 %(RH)

Atmospheric Pressure: 86 to 106 kPa

5.Appearance and Dimensions









※No Marking.

■Unit Mass (Typical value)

 $0.35\,\mathrm{g}$

(in mm)

6.Electrical Performance

No.	Item	Specification	Test Method
6.1	Inductance	Inductance shall meet item 3.	Measuring Equipment: KEYSIGHT 4192A or equivalent Measuring Frequency: 100kHz
6.2	DC Resistance	DC Resistance shall meet item 3.	Measuring Equipment: Digital multi meter
6.3	Self Resonant Frequency(S.R.F)	S.R.F shall meet item 3.	Measuring Equipment: KEYSIGHT E4991A or equivalent

7.Mechanical Performance

No.	Item	Specification	Test Method
7.1	Shear Test	Chip coil shall not be damaged.	Substrate: Glass-epoxy substrate Force: 10N Hold Duration: 5±1s Chip coil Substrate
7.2	Bending Test		Substrate: Glass-epoxy substrate (100×40×1.0mm) Speed of Applying Force: 0.5mm / s Deflection: 2mm Hold Duration: 5s Pressure jig
7.3	Vibration		Oscillation Frequency: 10 to 2000 to 10Hz for 20 minutes Total amplitude: 1.5 mm or Acceleration amplitude 98m/s²whichever is smaller. Testing Time: A period of 2 hours in each of 3 mutually perpendicular directions. (Total 6 hours)


Reference Only

No.	Item	Specification	Test Method
7.4	Solderability	The wetting area of the electrode shall be at least 90% covered with new solder coating.	Flux:Ethanol solution of rosin,25(wt)% (Immersed for 5s to 10s) Solder: Sn-3.0Ag-0.5Cu Pre-Heating:150±10°C / 60 to 90s Solder Temperature:240±5°C Immersion Time:3±1 s
7.5	Resistance to Soldering Heat	Appearance: No damage Inductance Change: within ±10%	Flux: Ethanol solution of rosin,25(wt)% (Immersed for 5s to 10s) Solder: Sn-3.0Ag-0.5Cu Pre-Heating: 150±10°C / 60 to 90seconds Solder Temperature: 270±5°C Immersion Time: 10±1 s Then measured after exposure in the room condition for 24±2 hours.

8.Environmental Performance (It shall be soldered on the substrate.)

No.	Item	Specification	Test Method
8.1	Heat Resistance	Appearance:No damage Inductance Change: within ±10%	Temperature: 85±2°C Time:1 000± 48 hours Then measured after exposure in the room condition for 24±2 hours.
8.2	Cold Resistance		Temperature: -40±2°C Time: 1000± 48 hours Then measured after exposure in the room condition for 24±2 hours.
8.3	Humidity		Temperature: 70±2°C Humidity: 90 to 95%(RH) Time: 1000± ⁴⁸ hours Then measured after exposure in the room condition for 24±2 hours.
8.4	Temperature Cycle		1 cycle: 1 step: -40±2°C / 30±3 min 2 step: Ordinary temp. / 10 to 15 min 3 step: +85±2°C / 30±3 min 4 step: Ordinary temp. / 10 to 15 min Total of 10 cycles Then measured after exposure in the room condition for 24±2 hours.

9. Specification of Packaging 9.1 Appearance and Dimensions of plastic tape



Dimension of the Cavity is measured at the bottom side.

9.2 Specification of Taping

- (1) Packing quantity (standard quantity)
 - 400 pcs / reel (φ180reel)
 - 1,500 pcs / reel (φ330reel)
- (2) Packing Method

Products shall be packed in the each embossed cavity of plastic tape and sealed by cover tape.

- (3) Sprocket hole
 - The sprocket holes are to the right as the tape is pulled toward the user.
- (4) Spliced point
 - Plastic tape and Cover tape has no spliced point.
- (5) Missing components number


Missing components number within 0.1 % of the number per reel or 1 pc., whichever is greater, and are not continuous. The specified quantity per reel is kept.

9.3 Pull Strength

Embossed carrier tape	10N min.	
Cover tape	5N min.	

9.4 Peeling off force of cover tape


Speed of Peeling off	300mm/min
Peeling off force	0.2 to 0.7N (minimum value is typical)




9.5 Dimensions of Leader-tape, Trailer and Reel

There shall be leader-tape(cover tape) and trailer-tape (empty tape) as follows.

« Packaging Code : L (φ180mm reel) »



« Packaging Code : K (φ330mm reel) »



Reference Only

9.6 Marking for reel

Customer part number, MURATA part number, Inspection number(*1), RoHS Marking(*2), Quantity etc · · ·

*1) < Expression of Inspection No.>

 $\frac{\square\square}{(1)} \frac{OOOO}{(2)} \frac{\times\!\times\!\times}{(3)}$

(1) Factory Code

(2) Date First digit : Year / Last digit of year

Second digit : Month / Jan. to Sep. \rightarrow 1 to 9, Oct. to Dec. \rightarrow O, N, D

Third, Fourth digit : Day

(3) Serial No.

*2) « Expression of RoHS Marking » ROHS – Y (△) (1) (2)


(1) RoHS regulation conformity parts.

(2) MURATA classification number

9.7 Marking for Outside package (corrugated paper box)

Customer name, Purchasing order number, Customer part number, MURATA part number, RoHS marking (*2) ,Quantity, etc · · ·

9.8. Specification of Outer Case



	Outer Case Dimensions (mm)			Standard Reel Quantity
	W	D	Н	in Outer Case (Reel)
φ180mm	186	186	93	4
φ330mm	340	340	95	4

Above Outer Case size is typical. It depends on a quantity of an order.

10. Caution

Limitation of Applications

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.

(1) Aircraft equipment

- (7) Traffic signal equipment
- (8) Disaster prevention / crime prevention equipment
- (2) Aerospace equipment(3) Undersea equipment
- (9) Data-processing equipment
- (4) Power plant control equipment
- (10) Applications of similar complexity and /or reliability requirements
- (5) Medical equipment
- to the applications listed in the above
- (6) Transportation equipment (vehicles, trains, ships, etc.)

11. Notice

This product is designed for solder mounting. (Reflow soldering only)


Please consult us in advance for applying other mounting method such as conductive adhesive.

11.1 Land pattern designing (Reflow Soldering)

Recommended land pattern for reflow soldering is as follows:

It has been designed for Electric characteristics and solderability.

Please follow the recommended patterns. Otherwise, their performance which includes electrical performance or solderability may be affected, or result to "position shift" in soldering process.





11.2 Flux, Solder

Flux	 Use rosin-based flux. Don't use highly acidic flux with halide content exceeding 0.2(wt)% (chlorine conversion value). Don't use water-soluble flux.
Solder	Use Sn-3.0Ag-0.5Cu solder Standard thickness of solder paste : 100µm to 150µm

Other flux (except above) Please contact us for details, then use.


11.3 soldering conditions (Reflow)

 Pre-heating should be in such a way that the temperature difference between solder and product surface is limited to 100°C max. Cooling into solvent after soldering also should be in such a way that the temperature difference is limited to 100°C max.

Insufficient pre-heating may cause cracks on the product, resulting in the deterioration of product quality.

 $\cdot\,$ Standard soldering profile and the limit soldering profile is as follows.

The excessive limit soldering conditions may cause leaching of the electrode and / or resulting in the deterioration of product quality.



	Standard Profile	Limit Profile	
Pre-heating	150~180°C	、90s±30s	
Heating	above 220°C、30s∼60s	above 230°C、60s max.	
Peak temperature	245±3°C	260°C,10s	
Cycle of reflow	2 times	2 time	

11.4 Reworking with soldering iron.

The following conditions must be strictly followed when using a soldering iron.


Pre-heating	150°C,1 min	
Tip temperature	380°C max.	
Soldering iron output	80W max.	
Tip diameter	ϕ 3mm max.	
Soldering time	3(+1,-0)s	
Times	2 times	

Note: Do not directly touch the products with the tip of the soldering iron in order to prevent the crack on the products due to the thermal shock.

11.5 Product's location

The following shall be considered when designing and laying out P.C.B.'s.

(1) P.C.B. shall be designed so that products are not subject to the mechanical stress due to warping the board.



11.6 Cleaning Conditions

Products shall be cleaned on the following conditions.

- (1) Cleaning temperature shall be limited to 60°C max.(40°C max for IPA.)
- (2) Ultrasonic cleaning shall comply with the following conditions with avoiding the resonance phenomenon at the mounted products and P.C.B.

Power: 20 W / I max. Frequency: 28kHz to 40kHz Time: 5 minutes max.

- (3) Cleaner
 - 1. Alternative cleaner
 - Isopropyl alcohol (IPA)
 - 2. Aqueous agent
 - •PINE ALPHA ST-100S
- (4) There shall be no residual flux and residual cleaner after cleaning.

In the case of using aqueous agent, products shall be dried completely after rinse with de-ionized water in order to remove the cleaner.

(5) Other cleaning

Please contact us.

11.7 Resin coating

The inductance value may change due to high cure-stress of resin to be used for coating/molding products.

An open circuit issue may occur by mechanical stress caused by the resin, amount/cured shape of resin, or operating condition etc. Some resin contains some impurities or chloride possible to generate chlorine by hydrolysis under some operating condition may cause corrosion of wire of coil, leading to open circuit.

So, please pay your careful attention when you select resin in case of coating/molding the products with the resin.

Prior to use the coating resin, please make sure no reliability issue is observed by evaluating products mounted on your board.

11.8 Caution for use

- Sharp material such as a pair of tweezers or other material such as bristles of cleaning brush, shall not be touched to the winding portion to prevent the breaking of wire.
- · Mechanical shock should not be applied to the products mounted on the board to prevent the breaking of the core.

11.9 Handling of a substrate

After mounting products on a substrate, do not apply any stress to the product caused by bending or twisting to the substrate when cropping the substrate, inserting and removing a connector from the substrate or tightening screw to the substrate.

Excessive mechanical stress may cause cracking in the product.



11.10 Storage and Handling Requirements

(1) Storage period

Use the products within 12 months after delivered.

Solderability should be checked if this period is exceeded.

(2) Storage conditions

· Products should be stored in the warehouse on the following conditions.

Temperature: -10 ~ 40°C

Humidity : 15 to 85% relative humidity No rapid change on temperature and humidity

The electrode of the products is coated with solder. Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solderability.

- Products should not be stored on bulk packaging condition to prevent the chipping of the core and the breaking
 of winding wire caused by the collision between the products.
- · Products should be stored on the palette for the prevention of the influence from humidity, dust and so on.
- · Products should be stored in the warehouse without heat shock, vibration, direct sunlight and so on.
- (3) Handling Condition

Care should be taken when transporting or handling product to avoid excessive vibration or mechanical shock.

12. **A** Note

- (1) Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
- (2) You are requested not to use our product deviating from the reference specifications.
- (3) The contents of this reference specification are subject to change without advance notice.

 Please approve our product specifications or transact the approval sheet for product specifications before ordering.