



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

MAXIM

Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

General Description


The MAX6018 is a precision, low-voltage, low-dropout, micropower voltage reference in a SOT23 package. This three-terminal reference operates with an input voltage from ($V_{OUT} + 200mV$) to 5.5V, and is available with output voltage options of 1.2V, 1.6V, 1.8V, and 2.048V.

The MAX6018 voltage reference consumes less than 5 μ A (max) of supply current and can source and sink up to 1mA of load current. Unlike conventional shunt-mode (two-terminal) references that waste supply current and require an external resistor, devices in the MAX6018 family offer a supply current that is virtually independent of supply voltage (with only 0.1 μ A/V variation with supply voltage) and do not require an external resistor. The MAX6018 has initial accuracies of 0.2% (A grade) and 0.4% (B grade) and temperature drift of 50ppm/ $^{\circ}$ C (max). The low-dropout voltage and the ultra-low, supply voltage-independent supply current make this device ideal for two-cell alkaline, end-of-life, battery-monitoring systems. The MAX6018 is available in a tiny 3-pin SOT23 package.


Applications

- Two-Cell, Battery-Operated Systems
- Battery-Operated Equipment
- Hand-Held Equipment
- Data-Acquisition Systems
- Industrial and Process-Control Systems

Typical Application Circuit



Pin Configuration



Features

- ♦ Ultra-Low Supply Current: 5 μ A (max)
- ♦ 1.6V Output from 1.8V Input
- ♦ Ultra-Small, 3-Pin SOT23 Package
- ♦ Initial Accuracy: $\pm 0.2\%$ (max)
- ♦ Low Temperature Drift: 50ppm/ $^{\circ}$ C (max)
- ♦ 200mV Dropout Voltage
- ♦ Load Regulation (1mA Source): 700 μ V/mA (max)
- ♦ Line Regulation ($V_{OUT} + 200mV$) to 5.5V: 250 μ V/V (max)
- ♦ Four Output Voltage Options: 1.2V, 1.6V, 1.8V, 2.048V

MAX6018

Ordering Information

PART	TEMP RANGE	PIN-PACKAGE	TOP MARK
MAX6018AEUR12-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJH
MAX6018BEUR12-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJI
MAX6018AEUR16-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJJ
MAX6018BEUR16-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJK
MAX6018AEUR18-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJL
MAX6018BEUR18-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJM
MAX6018AEUR21-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJN
MAX6018BEUR21-T	-40 $^{\circ}$ C to +85 $^{\circ}$ C	3 SOT23-3	FZJO

Selector Guide

PART	OUTPUT VOLTAGE (V)	INITIAL ACCURACY (%)
MAX6018AEUR12	1.263	± 0.2
MAX6018BEUR12	1.263	± 0.4
MAX6018AEUR16	1.600	± 0.2
MAX6018BEUR16	1.600	± 0.4
MAX6018AEUR18	1.800	± 0.2
MAX6018BEUR18	1.800	± 0.4
MAX6018AEUR21	2.048	± 0.2
MAX6018BEUR21	2.048	± 0.4

MAXIM

Maxim Integrated Products 1

For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.

Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

ABSOLUTE MAXIMUM RATINGS

(Voltages Referenced to GND)

V_{IN}	-0.3V to +6V
Output Short-Circuit Duration to GND or V_{IN}	Continuous
Continuous Power Dissipation ($T_A = +70^\circ\text{C}$)	
3-Pin SOT23 (derate 4.0mW/ $^\circ\text{C}$ above $+70^\circ\text{C}$)	320mW

Operating Temperature Range	-40°C to +85°C
Junction Temperature	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (soldering, 10s)	+300°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS (MAX6018_12–1.263V)

($V_{IN} = 1.8\text{V}$; $C_{OUT} = 47\text{nF}$, $I_{OUT} = 0$; $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ\text{C}$.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
OUTPUT						
Output Voltage	V_{OUT}	MAX6018A_12 (0.2%)	1.2605	1.2630	1.2655	V
		MAX6018B_12 (0.4%)	1.2580	1.2630	1.2681	
Output Voltage Temperature Drift	TCV_{OUT}	(Note 2)	16	50	100	$\mu\text{V}/^\circ\text{C}$
Line Regulation	$\Delta V_{OUT}/\Delta V_{IN}$	$1.8\text{V} \leq V_{IN} \leq 5.5\text{V}$	50	400	1000	$\mu\text{V/V}$
Load Regulation	$\Delta V_{OUT}/\Delta I_{OUT}$	$0 \leq I_{OUT} \leq 1\text{mA}$	90	700	1000	$\mu\text{V/mA}$
		$-100\mu\text{A} \leq I_{OUT} \leq 0$	2	9	100	$\mu\text{V}/\mu\text{A}$
Short-Circuit Current	I_{SC}	Sourcing to GND	3	10	100	mA
		Sinking from V_{IN}	6	10	100	
Long-Term Stability	$\Delta V_{OUT}/\Delta \text{Time}$	1000hrs at $T_A = +25^\circ\text{C}$	100	1000	10000	ppm
Thermal Hysteresis		(Note 4)	130	1000	10000	ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e_{OUT}	0.1Hz to 10Hz	45	100	1000	$\mu\text{V}_{\text{p-p}}$
		10Hz to 10kHz	100	1000	10000	μVRMS
Ripple Rejection		$V_{IN} = 1.8\text{V} \pm 100\text{mV}$ ($f = 120\text{Hz}$)	85	100	1000	dB
Turn-On Settling Time	t_R	Settling to 0.1%; $C_{OUT} = 5\text{nF}$	200	1000	10000	μs
Capacitive-Load Stability Range	C_{OUT}	(Note 2)	47	1000	10000	nF
INPUT						
Supply Voltage Range	V_{IN}	Guaranteed by Line Regulation Test	1.8	5.5	10	V
Quiescent Supply Current	I_{IN}	$T_A = +25^\circ\text{C}$	3	5	10	μA
		$T_A = T_{MIN}$ to T_{MAX}	3	6	10	
Change in Quiescent Supply Current vs. Input Voltage	$\Delta I_{IN}/\Delta V_{IN}$	$1.8\text{V} \leq V_{IN} \leq 5.5\text{V}$	0.1	0.5	1.0	$\mu\text{A/V}$

Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

ELECTRICAL CHARACTERISTICS (MAX6018_16–1.600V)

($V_{IN} = 1.8V$; $C_{OUT} = 47nF$, $I_{OUT} = 0$; $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^{\circ}C$.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
OUTPUT						
Output Voltage	V_{OUT}	MAX6018A_16 (0.2%)	$T_A = +25^{\circ}C$	1.5968	1.6000	1.6032
		MAX6018B_16 (0.4%)	$T_A = +25^{\circ}C$	1.5936	1.6000	1.6064
Output Voltage Temperature Drift	TCV_{OUT}	(Note 2)		16	50	ppm/ $^{\circ}C$
Line Regulation	$\Delta V_{OUT}/\Delta V_{IN}$	$1.8V \leq V_{IN} \leq 5.5V$		40	250	$\mu V/V$
Load Regulation	$\Delta V_{OUT}/\Delta I_{OUT}$	$0 \leq I_{OUT} \leq 1mA$		90	700	$\mu V/mA$
		$-750\mu A \leq I_{OUT} \leq 0$		0.6	50	$\mu V/\mu A$
Dropout Voltage (Note 3)	$V_{IN} - V_{OUT}$	$I_{OUT} = 1mA$		100	200	mV
Short-Circuit Current	I_{SC}	Sourcing to GND		6		mA
		Sinking from V_{IN}		2		
Long-Term Stability	$\Delta V_{OUT}/\text{Time}$	1000hrs at $T_A = +25^{\circ}C$		100		ppm
Thermal Hysteresis		(Note 4)		130		
DYNAMIC CHARACTERISTICS						
Noise Voltage	e_{OUT}	0.1Hz to 10Hz		40		μV_{p-p}
		10Hz to 10kHz		150		
Ripple Rejection		$V_{IN} = 1.8V \pm 100mV$ ($f = 120Hz$)		85		dB
Turn-On Settling Time	t_R	Settling to 0.1%; $C_{OUT} = 5nF$		200		
Capacitive-Load Stability Range	C_{OUT}	(Note 2)		0.1	1000	nF
INPUT						
Supply Voltage Range	V_{IN}	Guaranteed by Line Regulation Test		1.8	5.5	V
Quiescent Supply Current	I_{IN}	$T_A = +25^{\circ}C$		3	5	μA
		$T_A = T_{MIN}$ to T_{MAX}		3	6	
Change in Quiescent Supply Current vs. Input Voltage	$\Delta I_{IN}/\Delta V_{IN}$	$1.8V \leq V_{IN} \leq 5.5V$		0.1	0.5	$\mu A/V$

MAX6018

Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

ELECTRICAL CHARACTERISTICS (MAX6018_18-1.800V)

($V_{IN} = 2.0V$; $C_{OUT} = 47nF$, $I_{OUT} = 0$; $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^{\circ}C$.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
OUTPUT						
Output Voltage	V_{OUT}	MAX6018A_18 (0.2%)	$T_A = +25^{\circ}C$	1.7964	1.8000	1.8036
		MAX6018B_18 (0.4%)	$T_A = +25^{\circ}C$	1.7928	1.8000	1.8072
Output Voltage Temperature Drift	TCV_{OUT}	(Note 2)		16	50	ppm/ $^{\circ}C$
Line Regulation	$\Delta V_{OUT}/\Delta V_{IN}$	$2.0V \leq V_{IN} \leq 5.5V$		40	275	$\mu V/V$
Load Regulation	$\Delta V_{OUT}/\Delta I_{OUT}$	$0 \leq I_{OUT} \leq 1mA$		90	800	$\mu V/mA$
		$-1mA \leq I_{OUT} \leq 0$		0.4	50	$\mu V/\mu A$
Dropout Voltage (Note 3)	$V_{IN} - V_{OUT}$	$I_{OUT} = 1mA$		100	200	mV
Short-Circuit Current	I_{SC}	Sourcing to GND		7.5		mA
		Sinking from V_{IN}		3		
Long-Term Stability	$\Delta V_{OUT}/\Delta$ Time	1000hrs at $T_A = +25^{\circ}C$		100		ppm
Thermal Hysteresis		(Note 4)		130		ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e_{OUT}	0.1Hz to 10Hz		45		μV_{p-p}
		10Hz to 10kHz		160		$\mu VRMS$
Ripple Rejection		$V_{IN} = 2.0V \pm 100mV$ ($f = 120Hz$)		85		dB
Turn-On Settling Time	t_R	Settling to 0.1%; $C_{OUT} = 5nF$		200		μs
Capacitive-Load Stability Range	C_{OUT}	(Note 2)		0.1	1000	nF
INPUT						
Supply Voltage Range	V_{IN}	Guaranteed by Line Regulation Test		2.0	5.5	V
Quiescent Supply Current	I_{IN}	$T_A = +25^{\circ}C$		3	5	μA
		$T_A = T_{MIN}$ to T_{MAX}		3	6	
Change in Quiescent Supply Current vs. Input Voltage	$\Delta I_{IN}/\Delta V_{IN}$	$2V \leq V_{IN} \leq 5.5V$		0.1	0.5	$\mu A/V$

Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

ELECTRICAL CHARACTERISTICS (MAX6018_21–2.048V)

($V_{IN} = 2.25V$; $C_{OUT} = 47nF$, $I_{OUT} = 0$; $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted. Typical values are at $T_A = +25^\circ C$.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
OUTPUT						
Output Voltage	V_{OUT}	$MAX6018A_21$ (0.2%)	$T_A = +25^\circ C$	2.0439	2.0480	2.0521
		$MAX6018B_21$ (0.4%)	$T_A = +25^\circ C$	2.0398	2.0480	2.0562
Output Voltage Temperature Drift	TCV_{OUT}	(Note 2)		16	50	$\text{ppm}/^\circ C$
Line Regulation	$\Delta V_{OUT}/\Delta V_{IN}$	$2.25V \leq V_{IN} \leq 5.5V$		45	330	$\mu\text{V}/V$
Load Regulation	$\Delta V_{OUT}/\Delta I_{OUT}$	$0 \leq I_{OUT} \leq 1\text{mA}$		90	1000	$\mu\text{V}/\text{mA}$
		$-1\text{mA} \leq I_{OUT} \leq 0$		0.3	50	$\mu\text{V}/\mu\text{A}$
Dropout Voltage (Note 3)	$V_{IN} - V_{OUT}$	$I_{OUT} = 1\text{mA}$	100	200		mV
Short-Circuit Current	I_{SC}	Sourcing to GND	10			mA
		Sinking from V_{IN}	4			
Long-Term Stability	$\Delta V_{OUT}/\text{Time}$	1000hrs at $T_A = +25^\circ C$		100		ppm
Thermal Hysteresis		(Note 4)	130			ppm
DYNAMIC CHARACTERISTICS						
Noise Voltage	e_{OUT}	0.1Hz to 10Hz	50			$\mu\text{V}_{\text{p-p}}$
		10Hz to 10kHz	175			μVRMS
Ripple Rejection		$V_{IN} = 2.25V \pm 100\text{mV}$ ($f = 120\text{Hz}$)	85			dB
Turn-On Settling Time	t_R	Settling to 0.1%; $C_{OUT} = 5\text{nF}$	200			μs
Capacitive-Load Stability Range	C_{OUT}	(Note 2)	0.1	1000		nF
INPUT						
Supply Voltage Range	V_{IN}	Guaranteed by Line Regulation Test	2.25	5.5		V
Quiescent Supply Current	I_{IN}	$T_A = +25^\circ C$	3	5		μA
		$T_A = T_{MIN}$ to T_{MAX}	3	6		
Change in Quiescent Supply Current vs. Input Voltage	$\Delta I_{IN}/\Delta V_{IN}$	$2.25V \leq V_{IN} \leq 5.5V$	0.1	0.5		$\mu\text{A}/\text{V}$

Note 1: Devices are 100% production tested at $T_A = +25^\circ C$ and are guaranteed by design from $T_A = T_{MIN}$ to T_{MAX} .

Note 2: Not production tested. Guaranteed by design.

Note 3: Dropout voltage is the minimum input voltage at which V_{OUT} changes $\leq 0.2\%$ from V_{OUT} at rated V_{IN} and is guaranteed by Load Regulation Test.










Note 4: Thermal hysteresis is defined as the change in $T_A = +25^\circ C$ output voltage before and after temperature cycling of the device (from $T_A = T_{MIN}$ to T_{MAX}). Initial measurement at $T_A = +25^\circ C$ is followed by temperature cycling the device to $T_A = +85^\circ C$ then to $T_A = -40^\circ C$ and another measurement at $T_A = +25^\circ C$ is compared to the original measurement at $T_A = +25^\circ C$.

MAX6018

Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

Typical Operating Characteristics

($T_A = +25^\circ\text{C}$, unless otherwise noted.)












Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

Typical Operating Characteristics (continued)

($T_A = +25^\circ\text{C}$, unless otherwise noted.)




MAX6018



Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

Typical Operating Characteristics (continued)

($T_A = +25^\circ\text{C}$, unless otherwise noted.)



Detailed Description

The MAX6018 is a precision, low-voltage, low-dropout, micropower, bandgap voltage reference in a SOT23 package. This three-terminal reference operates with an input voltage from ($V_{\text{OUT}} + 200\text{mV}$) to 5.5V, and is available with output voltage options of 1.2V, 1.6V, 1.8V, and 2.048V. These devices can source up to 1mA with $<200\text{mV}$ of dropout voltage, making them attractive for use in low-voltage applications.

Applications Information

Output/Load Capacitance

These devices require a minimum of 100pF load to maintain output stability.

They remain stable for capacitive loads as high as 1 μF . In applications where the load or the supply can experience step changes, a larger output capacitor reduces the amount of overshoot (or undershoot) and assists the circuit's transient response. Otherwise, applications may not need more than 100pF.

Supply Current

The 5 μA maximum supply current varies only 0.1 $\mu\text{A}/\text{V}$ with the supply voltage.

When the supply voltage is below the minimum-specified input voltage (as during turn-on), the devices can draw up to 20 μA beyond the nominal supply current. The input voltage source must be capable of providing this current to ensure reliable turn-on.

Pin Description

PIN	NAME	FUNCTION
1	IN	Supply Voltage Input. Bypass with a 0.1 μF capacitor to ground.
2	OUT	Reference Voltage Output. Bypass with at least 100pF to ground. (See <i>Output/Load Capacitance</i> section).
3	GND	Ground

Turn-On Time

These devices typically turn on and settle to within 0.1% of their final value in 200 μs . The turn-on time can increase up to 1ms with the device operating at the minimum dropout voltage and the maximum load.

Chip Information


TRANSISTOR COUNT: 87

PROCESS: BiCMOS

Precision, Micropower, 1.8V Supply, Low-Dropout, SOT23 Voltage Reference

Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to www.maxim-ic.com/packages.)



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600

9

MAX6018