

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







NOTES:					O Z
1.0 ELECTRICAL SPECIFICATIONS:	2.0 FINISHING:	MIDWEST MODEL NUMBER	POWER (WATTS)		MODEL
1.1 FREQUENCY RANGE: 1.0 to 4.0 GHz	2.1 GREY PER MIL—E—15090 TYPE II, CLASS 2 OVER MIL—C—5541 CLASS 3A	CPL-5221-XX-NNN-79 COUPLING	INPUT R	REF. PEAK	
1.2 COUPLING: SEE TABLE 1.3 FREQUENCY SENSITIVITY: ±0.6dB 1.4 DIRECTIVITY: 20dB MIN. 1.5 VSWR (MAX): 1.30:1 1.6 INSERTION LOSS: 0.6dB MAX. (EXCLUDING COUPLED POWER)	MEETS MIL-F-14072 MEETS MIL-E-5400	CPL-5221-06-NNN-79 6 ±1.0dB	50	10 4000	NUMBER 5221-XX
		CPL-5221-10-NNN-79 10 ±1.0dB	50	10 4000	× F
	2.2 MARKING: MARK UNIT AS SHOWN (REF.: SLK-08029-82-[40-43])	CPL-5221-16-NNN-79 16 ±1.0dB	50	40 4000	
		CPL-5221-20-NNN-79 20 ±1.0dB	50	50 4000	
1.7 POWER: SEE TABLE	3.0 DIMENSIONS IN PARENTHESIS ARE IN MILLIMETERS.				79
1.8 RF IMPEDANCE: 50 OHMS	IN WILLIMETERS.				REV - 1
1.9 WEIGHT (MAX): 10.4 oz	1.70(110.4)	75(10.1)			<u> </u>
	4.70(119.4)	75(19.1) (3 PLCS)			
	.55(14.0) - 3.60(91.4) -				
	2.35(59.7)				
		0.5(12.7)			
TYPE N JACK		MAX.			
PER MIL-PRF-3	39012			 -	
TYP (3 PLCS)	XXdB O				
\downarrow OUTPUT \downarrow OUTPUT \downarrow OF (24.1) 1.35					
.55	INPUT MFR 34078	─────────── .55(21.1) (32	1.3)		
(14.0		OUTPUT			
→			<u>'</u>		
	.55(14.0) — 3.60(91.4) —			.38(9	16)
		.23(3.1)		.50(5	,.0)
	<u> </u>	✓ ø.147(3.7) THRU		.75	(19.1)
		TYP. (3 PLCS.)			
2/23/98 4/22/05		UNLESS OTHERWISE 34078 MID	WEST	MICROW	4VE
D D D D D D D D D D D D D D D D D D D		ARE IN INCHES AND	TITLE		
		TOLERANCES ARE: NOTICE: The information contained in this	on		
DESCRIPTION LEASED D TILEBLOCK O TILEBLOCK	MIDWEST MICROWAVE CPL-5221-XX-NNN-79	3 PLACE DECIMALS ±.005 drawing is proprietary		IONAL COUPLE	R
SCR SED	FREQ. 1.0-4.0 GHz	without the permission			
		PARALIFLITY: TIR	DBAURNO AND TO		
 		FLATNESS: T.I.R	DRAWING NUMBER CPL-5221-	ER -XX-NNN-79	
	BACKSIDE MARKING	CONCENTRICITY: T.I.R CHECKED/DATE APPROVED/DATE ANGLES AND PERPENDICULARITY: ±1*	SCALE: 1=		of 1
[-1]		ANGLES AND PERPENDICULARITY #1	JOALE. -	1 Janeer 1	<u> </u>