



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





#### General ordering data

Order No.	1805790000
Part designation	SFC 2/21 NEUTRAL RT
Version	Conductor markers, L x W: 21 x 4 mm, Polyamide, red
EAN	4032248273522
Qty.	120 pc(s).

#### Markings

Cadmium	no
Can be labelled with thermal transfer printers	No
Can be printed with plotter	Yes
Can be written with dot-matrix printer	No
Can be written with laser printer	No
Conductor O.D., max.	5 mm
Conductor O.D., min.	3 mm
Conductor cross-section, max.	4 mm <sup>2</sup>
Conductor cross-section, min.	2.5 mm <sup>2</sup>
Function	Conductor and cable markers
Halogen	no
Height	7 mm
Insulation cross-section, max.	5 mm
Length	21 mm
Material	Polyamide
Material colour	red
Material colour according to resistance code	2
Max. temperature, continuous	100 °C
Min. temperature, continuous	-40 °C
Pin can be written (STI)	Yes
PrintJet	Yes
Printed characters	without
Silicone	no
Speed marking laser	Yes
Type of printing	Neutral
UL 94 flammability class	V2

#### Markings

Width 4 mm

#### Approvals

Approvals institutes n.a.

#### Classifications

ETIM 2.0	EC001530
ETIM 3.0	EC001530
eClass 4.1	24-19-02-19
eClass 5.0	27-14-91-03
eClass 5.1	27-14-91-03

#### Similar products

Order No.	Part designation	Version
1813200000	SFC 0/21 NEUTRAL RT	Conductor markers, L x W: 21 x 4 mm, Polyamide, red
1779080003	SFC 1/21 NEUTRAL RT	Conductor markers, L x W: 21 x 4 mm, Polyamide, red
1025290000	SFC 3/21 MC NE RT	Conductor markers, L x W: 21 x 4 mm, Polyamide, red