

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China












### PHYSICAL DIMENSIONS:

A 31.50 MAX28.00 MAX 19.00 MAX. 25.00 REF 0.25 6.00 0.25 3.35 0.30 15.24 0.30 24.20







### ELECTRICAL SPECIFICATION

ELECTRICAL CHARACTERISITICS		NOM	MIN	MAX
INDUCTANCE @ 100KHz/100mV 1-4/2-3	uΗ	1300	780	1755
DCR 1-4/2-3	$\Omega$			10
RATING CURRENT	А			11
RATING VOLTAGE	Vrms			250


HIPOT COIL-COIL: 1500VAC

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 2. TIN: LEAD-FREE SOLDER BAR.
- 3. BASE MATERIAL: PHENOLIC RESIN.
- 4. THIS PART HAS NO PIN POLARITY.
- 5. OPERATION TEMPERATURE RANGE: -40°C TO +125°C (INCLUDING SELF-HEATING).

### **EQUIVALENT CIRCUIT**

# Z, R , XL vs. FREQUENCY



### LAND PATTERNS FOR REFLOW SOLDERING






## В ADD BOTTOM VIEW AND NOTE 3 ORIGINAL DRAFT

DESCRIPTION

REV


### RECOMMENDED SOLDERING CONDITIONS



This print is the property of Laird			S ARE IN mm .	DIMENSIONS
Tech. and is loaned in confidence subject to return upon request and				
with the understanding that no				
copies shall be made without the written consent of Laird Tech. All				
rights to design or invention are				
reserved.				
PROJECT/PART NUMBER:				
ਜ਼ CMX1211X132B-10 L	OILL	03/11/13	OLTACE LIMIT	CHANCE BATING VO

11/14/12 QIU

DATE INT





QIU SHEET: NTS 1 of 1 ГСМХ1211Х132B-10-С

AGILENT E4991A RF Impedance/Material Analyzer HP 16092A Test Fixture.