

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







IC1206A332R-10

PHYSICAL DIMENSIONS:

A 3.20 [.126] ± 0.20[.008]

B 1.60 [.063] ± 0.20[.008]

C 1.10 [.043] ± 0.30[.012]

D 0.50 [.020] ± 0.30[.012]

B

UNCONTROLLED DOCUMENT


NOTES: UNLESS OTHERWISE SPECIFIED

- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 3000 PCS/REEL, EMBOSSED PLASTIC TAPE.
- 2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
- 5. I (OPERATING) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MINIMUM INDUCTANCE (L).
- 6. OPERATING TEMP. RANGE: -40°C~+125°C. (INCLUDING SELF-HEATING)

ELECTRICAL CHARACTERISTICS:


	3,630 Max				
L (nH) ± 10%	3,300	Nom			
	2,970	Min@ 50mA			
Q (Min)	45				
Freq. (MHz)	10				
Self-Resonant Freq (MHz)	4	1			
DCR(Max) Ω	0.70				
l (Max)	150mA				
I (Operating)	50m A				

LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 (0.030) to this dimension)

RECOMMENDED SOLDERING CONDITIONS





	DIMENSIONS ARE IN mm [INCHES]. This print is the property of Laird									
Γ					Tech, and is loaned in confidence subject to return upon request (_	=	.
t					with the understanding that no		•	7		
İ					copies shall be made without the written consent of Laird Tech. A		Laird			
t					rights to design or invention are					
t					reserved.					
ŀ					PROJECT/PART NUMBER:	R	ΕV	PART TY	PE:	DRAWN BY:
	С	ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	08/05/13	QU	IC1206A332R-10		С	co-	-FIRE	JRK
ŀ										
1	В	UPDATE COMPANY LOGO	06/24/08	JRK	PATE: 01/03/07	SCALE	NIS		SHEET:	
ſ	Α	ORIGINAL DRAFT	01/03/07	JRK	, ,					
ŀ	REV	DESCRIPTION	DATE	INT	IC1206A332R-10-C	TOOL	٠.	_	2	of 2