



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Datasheet for part number CIR06R-36-10SF80

|   |
|---|
| Our Catalog Part Number: CIR06R-36-10S-F80  |
| Our Global Manufacturing Part Number: 000212040   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

| Product Datasheet                                  |  |
|--|--|
| SERIES   | Connector with Bayonet Coupling  |
| Shell Style  | Straight Plug Connector  |
| Environmental Class                                | Backshell includes wire sealing grommet and compression ring   |
| Shell Size   | 36   |
| Contact Arrangement                                | 36-10  |
| Total Number of contacts                           | 48 contacts  |
| Number of Contacts Size 16                         | 48 contacts size 16  |
| Gender   | Socket   |
| Contact Type                                       | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating                                    | Silver   |
| Shell Material                                     | Aluminium alloy  |
| Shell Plating                                      | Olive drab chromate over cadmium plating (conductive)  |
| Wire Size Cross Section for Contacts Size 16       | 1,0-1,5 mm <sup>2</sup> or AWG 18-16   |
| Contact Rating for Contacts Size 16                | Maximum Current = 22 A<br>Rated and Test Current = 13 A<br>Potential Drop max. 74 mV   |
| Shock Resistance                                   | Waterproof to 10 meteres (33 ft)<br>12 h (14.7 PSI)  |
| Coupling   | 2000 couplings minimum   |
| Service Rating Letter                              | A  |
| Operating Voltage DC                               | 700 V  |
| Operating Voltage AC                               | 500 V  |
| Dielectric strength - Minimum Flashover AC RMS     | 2800 V   |
| Dielectric strength - Test Voltage AC RMS (Hi Pot) | 2000 V   |
| Note   | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General  | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |