



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RPC-2.40

Mismatch
Plug

09S150-075S3



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to
Mechanically compatible with

IEC 61169-40
RPC-1.85

Documents

Application note

AN001 "Calibration Services"

Material and plating

Connector parts

Center contact
Outer contact
Coupling nut
Dielectric
Substrate

Material

Beryllium copper
Stainless steel
Stainless steel
PS
Al₂O₃

Plating

Gold, min. 1.27 µm, over nickel
Passivated
Passivated

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/09.14/6.2

Technical Data Sheet				Rosenberger			
RPC-2.40		Mismatch Plug		09S150-075S3			
Electrical data							
Frequency		DC to 50 GHz					
Return loss		≥ 1.5 ± 0.07, DC to 20 GHz					
		≥ 1.5 ± 0.13, 20 GHz to 50 GHz					
DC Resistance		75 Ω ± 0.375 Ω					
Power handling (at 25 °C, sea level)		≤ 0.5 W, derated linearity by 0.005 W/K					
Mechanical data							
Mating cycles		≥ 500					
Maximum torque		1.65 Nm					
Recommended torque		0.90 Nm					
Gauge		0.00 mm to 0.03 mm					
Environmental data							
Operating temperature range ¹		+20 °C to +26 °C					
Rated temperature range of use ²		0 °C to +50 °C					
Storage temperature range		- 40 °C to +85 °C					
RoHS		compliant					
¹ Temperature range over which these specification are valid.							
² This range is underneath and above the operating temperature range, within the mismatch is fully functional and could be used without damage.							
Declaration of calibration options							
Factory Calibration							
Standard delivery for this calibration standard includes a Factory Calibration. The Calibration Certificate issued reports individual calibration results, traceable to national / international standards.							
Accredited Calibration							
Not available.							
For further, more detailed information see application note AN001 on the Rosenberger homepage.							
Calibration interval							
Recommendation		12 months					
Packing							
Standard		1 pce in box					
Weight		6.7 g/pce					
While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.							
Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marion Striegler	19.08.14	Markus Müller	20.07.18	c00	18-1027	Marion Striegler	20.07.18
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 2 / 2	