



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RF_35/09.14/6.2 Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

Technical Data Sheet		Rosenberger	
RPC-N 75 Ω	Calibration Kit Jack	P5K30R-MSOTS3	
<div></div>			
All dimensions are in mm; tolerances according to ISO 2768 m-H			
Interface		IEC 61169-16	
According to			
Contents and Documentation			
This kit is delivered with			
<ul style="list-style-type: none">• Standard Definitions Card Printed Standard Definitions that can be used on nearly all Vector Network Analyzers• Test Results Documentation• Lanyard• Hard Shell Case			
Material and plating			
Connector parts			
Center conductor	Material	Plating	
Outer conductor	CuBe	Gold, min. 1.27 µm, over nickel	
Body	Stainless steel	Passivated	
Dielectric	Aluminum	black anodized	
Substrate	PS		
	Al ₂ O ₃		
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de		Tel. : +49 8684 18-0 Email : info@rosenberger.de	
		Page 1 / 3	

Electrical data

Frequency range DC to 12 GHz

Thru

Return loss
 ≥ 36 dB, DC to 4 GHz
 ≥ 27 dB, 4 GHz to 8 GHz
 ≥ 25 dB, 8 GHz to 12 GHz

Open

Error from nominal phase¹
 $\leq 3.0^\circ$, DC to 4 GHz
 $\leq 5.0^\circ$, 4 GHz to 8 GHz
 $\leq 6.0^\circ$, 8 GHz to 12 GHz

Short

Error from nominal phase²
 $\leq 2.5^\circ$, DC to 4 GHz
 $\leq 4.0^\circ$, 4 GHz to 8 GHz
 $\leq 5.0^\circ$, 8 GHz to 12 GHz

Load

Return loss
 ≥ 38 dB, DC to 4 GHz
 ≥ 32 dB, 4 GHz to 8 GHz
 ≥ 30 dB, 8 GHz to 12 GHz

DC-Resistance 75 Ω ± 0.75 Ω

Power handling ≤ 1.0 W

¹ The nominal phase is defined by the Offset Delay, the Offset Loss and the Fringing Capacitances

² The nominal phase is defined by the Offset Delay, the Offset Loss and the Short Inductance

Mechanical data

Mating cycles ≥ 500
 Maximum torque 1.70 Nm
 Recommended torque 1.10 Nm
 Gauge 5.18 mm to 5.26 mm

General standard definitions

For proper operation the vector network analyzer (VNA) needs a model describing the electrical behaviour of this calibration standard. The different models, units, and terms used will depend on the VNA type and they will have to be entered into the VNA. All values are based on typical geometry and plating.

Thru

Offset Z_o / Impedance / Z_o 75 Ω
 Offset Delay 153.106 ps
 Length (electrical) / Offset Length 45.90 mm
 Offset Loss 1.20 GΩ/s
 Loss 0.0106 dB/√GHz
 Line Loss @ 1GHz 0.0002 dB/mm

Open

Offset Z_o / Impedance / Z_o 75 Ω
 Offset Delay 41.095 ps
 Length (electrical) / Offset Length 12.32 mm
 Offset Loss 1.20 GΩ/s
 Loss 0.0057 dB/√GHz
 Fringing Capacitances
 $C_0 = 8.50000 \times 10^{-15}$ F / 8.50000 fF
 $C_1 = 9950.00 \times 10^{-27}$ F/Hz / 9.95000 fF /GHz
 $C_2 = -2190.00 \times 10^{-36}$ F/Hz² / -2.19000 fF /GHz²
 $C_3 = 107.000 \times 10^{-45}$ F/Hz³ / 0.10700 fF /GHz³

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/09.14/6.2

Technical Data Sheet				Rosenberger			
RPC-N 75 Ω		Calibration Kit Jack		P5K30R-MSOTS3			
Short							
Offset Z _o / Impedance / Z _o		75 Ω					
Offset Delay		41.095 ps					
Length (electrical) / Offset Length		12.32 mm					
Offset Loss		1.20 GΩ/s					
Loss		0.0057 dB/√GHz					
Short Inductance		L ₀ = -54.0000 x 10 ⁻¹² H / -54.0000 pH					
		L ₁ = 9950.00 x 10 ⁻²⁴ H/Hz / 9.95000 pH/GHz					
		L ₂ = 970.000 x 10 ⁻³³ H/Hz ² / 0.97000 pH/GHz ²					
		L ₃ = -115.000 x 10 ⁻⁴² H/Hz ³ / -0.11500 pH/GHz ³					
Load							
Offset Z _o / Impedance / Z _o		75 Ω					
Offset Delay		0.0000 ps					
Length (electrical) / Offset Length		0.000 mm					
Offset Loss		0.00 GΩ/s					
Loss		0.0000 dB/√GHz					
Environmental data							
Operating temperature range ³		+20 °C to +26 °C					
Rated temperature range of use ⁴		0 °C to +50 °C					
Storage temperature range		-40 °C to +85 °C					
RoHS		compliant					
³ Temperature range over which these specifications are valid.							
⁴ This range is underneath and above the operating temperature range, within the calibration kit is fully functional and could be used without damage							
Declaration of documentation							
Standard delivery for this kit includes Test Results. The documentation issued reports which quantities were tested individually, traceable to national / international standards. Model based standard definitions of the calibration standards are reported in Agilent / Keysight, Rohde & Schwarz and Anritsu compatible VNA format.							
Inspection interval							
Recommendation		12 months					
Packing							
Standard		1 pce in bag					
Weight		255 g/pce					
While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.							
Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	14.01.16	Markus Müller	26.10.17	d00	17-1795	Marion Striegler	26.10.17
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Email : info@rosenberger.de			Page 3 / 3