



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



B45196H, Tantalum, MnO2 Tantalum, 0.22 uF, 20%, 50 V, SMD, Molded, 3216, Height Max = 1.8mm

**General Information**

<b>Supplier:</b>	KEMET
<b>Series:</b>	B45196H
<b>Dielectric:</b>	MnO2 Tantalum
<b>Style:</b>	SMD Chip
<b>Description:</b>	SMD, Molded
<b>RoHS:</b>	Yes
<b>Termination:</b>	Tin
<b>Notes:</b>	Obsolete. Old Part Number [Obsolete] Was B45196H7224M109

**Dimensions**

<b>Footprint</b>	3216
<b>L</b>	3.2mm +/-0.2mm
<b>W</b>	1.6mm +/-0.2mm
<b>H</b>	1.6mm +/-0.2mm
<b>S</b>	0.8mm +/-0.3mm
<b>F</b>	1.2mm +/-0.1mm
<b>K</b>	1.3mm TYP

**Specifications**

<b>Capacitance:</b>	0.22 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	50 VDC (85C), 33.5 VDC (125C)
<b>Temperature Range:</b>	-55/+125C
<b>Rated Temperature:</b>	85C
<b>Dissipation Factor:</b>	4%
<b>Failure Rate:</b>	N/A
<b>Leakage Current:</b>	0.5 uA

**Packaging Specifications**

<b>Packaging:</b>	T&R, 178mm
<b>Packaging Quantity:</b>	2000