

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China










TETRA M8 Vehicle Base & Whip

Antennas



The new Laird Technologies M8 vehicle mount for TETRA whip antennas reaffirms a commitment to the Public Safety and Land Mobile Radio market. The M8 vehicle mount base is an industry standard and whip antennas can be easily interchanged due to the modularity of the design.

The Laird Technologies M8 base and whips are molded with high impact, UV resistant polycarbonate material and use high-quality coaxial cables and connectors.

FEATURES FROMS

- Designed for rugged environments
- Rigid stainless steel or flexible molded whips
- Easy to install both inside and outside the vehicle
- Modular design for interchangeability
- Multiple cable types & connector

APPLICATIONS

• Public Safety



- PMR
- TETRA & TETRAPOL

SPECIFICATIONS

BASE	
Height Above Ground	23 mm
Installation Hole Dia	18 mm
Operating Temperature	-40°C - 85°C
Body Material	HDPE (UV Stabilized)
Lock Material	Stainless Steel
Gasket Material	PU UV Grade
Hardware Material	Stainless Steel
Color	Black
Cable Type	RG58A/U other options are available
Connector	Interchangeable

ANTENNA			
Pattern	Omni-Directional		
Maximum Power	50 Watts		
Nominal Impedance	50 Ohm		
Polarization	Vertical		
VSWR	2.0:1 measured at feed point		
Termination	M8		
Ground Plane	Ground Plane Dependant		
Color	Black		
Material	Rigid Whip: 17-7PH Stainless Steel Flexible Whip: Polyurethane Injection Molded		



Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +44.(0).1628.858941 IAS-EUSales@lairdtech.com Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

www.lairdtech.com





BASE SPECIFICATIONS

PART NUMBER	CABLE TYPE	CABLE LENGTH	CONNECTOR
MTEN350NA-001	ATX195 (low loss RG58)	3.5m (11.48ft)	
MTEN500NA-001	ATX195 (low loss RG58)	5m (16.40ft)	
MTEF350NA-001	RG58A/U	3.5m (11.48ft)	No Connector
MTEF500NA-001	RG58A/U	5m (16.40ft)	(multiple connectors available)
MTEG350NA-001	RG58U	3.5m (11.48ft)	,
MTEG500NA-001	RG58U	5m (16.40ft)	

ANTENNA SPECIFICATIONS

MODEL	FREQUENCY RANGE (MHZ)	PEAK GAIN	OVERALL ANTENNA HEIGHT
Rigid Whip Series			
WFB300	300 MHz - 334 MHz	2 dBi	8.91 in / 22.6 cm
WFB350	350 MHz - 370 MHz	2 dBi	7.75 in / 19.7 cm
WFB380	380 MHz - 430 MHz	2 dBi	6.91 in / 17.6 cm
WFB450	450 MHz - 470 MHz	2 dBi	6.16 in / 15.7cm
WFB480	480 MHz - 520 MHz	2 dBi	5.66 in / 14.4 cm
Flexible Whip Series			
EXC3001M8-001	300 MHz - 334 MHz	2 dBi	8.25 in / 21.0 cm
EXC3501M8-001	350 MHz - 370 MHz	2 dBi	7.50 in / 19.1 cm
EXC3801M8-001	380 MHz - 430 MHz	2 dBi	6.62 in / 16.8 cm
EXC4501M8-001	450 MHz - 470 MHz	2 dBi	6.06 in / 15.4cm
EXC4801M8-001	480 MHz - 520 MHz	2 dBi	5.50 in / 14 cm